



# ViewStation® Videoconferencing Accessories

Offering a complete line of accessories for all of your conferencing needs

Polycom® offers a complete line of accessories to compliment your award winning ViewStation™ videoconferencing system. With top of the line accessories such as Sony® Trinitron® monitors and Canon® document cameras, Polycom provides you with a total solution for all your videoconferencing needs.



## Sony Trinitron® Monitors



Recommended for best performance with the ViewStation™ system. The vertically flat picture tube, Sony® Trinitron® technology and 'S' video deliver the best picture quality.

- 41" S-Video - NTSC Monitor . . . . .2583-08400-001
- 32" S-Video - NTSC Monitor . . . . .2583-08400-002
- 27" S-Video - NTSC Monitor . . . . .2583-08400-003

(Note: all dimensions are diagonal)


## Hard Shell Carrying Case



Ideal for ViewStations on the go! Custom-designed hard shell carrying case protects the ViewStation during transportation. Custom foam inserts surrounds the unit. The case provides adequate space for cables and accessory components.

- Hard shell carrying case . . . . .2676-08404-001

## Video Labs Monitor Cart



A functional and cost effective solution for supporting a ViewStation and TV monitor. Finished in a textured black paint, the monitor cart has 4" wheels and an interior adjustable or removable shelf. Unit includes dual smoked Plexiglass doors with magnetic catches and a 2" x 12" slot in the top surface for wiring purposes.

- 27" Monitor Cart 27" x 28.5" x 31" . .2583-08401-003
- 32" Monitor Cart 32" x 28.5" x 31" . .2583-08401-002

Units ship completely assembled and ready for installation

## Kensington Masterlock Security Cable



Protect your investment with a secure cable that attaches to a slot built in to the back of the ViewStation unit.

- Kensington® Master Lock® Security Cable . . . . .2457-08403-001

**Canon® Document Cameras**



Ideal for presenting documents, graphics, 3-D objects and other media to your audience with 450-line resolution. The Video Visualizer RE-350 features 12 x power zoom, auto focus, auto light control, negative/positive image conversion, anti-flicker reduction, built-in overhead and backlight lamps and automatic white balance. Includes an S-video connection cable.



The VIZCAM 1000 features a 3-Axis positioning arm for limitless camera shots and angles, negative/positive image conversion, and macro viewing capabilities up to 5/16".

- Canon® Visualizer NTS-R350 . . . . .2624-08413-001
- Canon® VIZCAM 1000 . . . . .2624-08413-002

**Sony Camera EVI-D30/D31 NTSC/PAL Camera**



Pan/tilt video camera with highly sophisticated image processing technology which enables target objects to be recognized. Features include: high speed, wide range, pan/tilt; X12 optical zoom, high speed auto-focus lens; 6-position preset; auto-tracking/ motion detector; and RS-232C serial control (VISCA). Includes AC Commander.

- Sony EVI-D30/31 Camera . . . . .1624-10307-002

**VideoLabs DocCam Pro VC**



Integrated scan converter makes PC output compatible with standard NTSC and PAL video formats. 16x Power Zoom Lens for extreme close-up viewing with razor sharp focus. Features a 180 degree rotating camera head or use as an auxiliary/presentation room camera. Telescoping neck

enables the user to extend the camera's neck to view large objects or objects at a distance. Auto focus/iris/shutter/white balance means less setup. Flexible LED top lighting provides natural white light and maintenance-free use. Remote control allows the user to roam during the presentation or videoconference.

- DocCam Pro VC/NTSC . . . . .1310-09097-004
- DocCam Pro VC/PAL . . . . .1310-09097-005

**Focus Enhancements TView Pro AV Video Scan Converter**



Easily and economically record high resolution computer-generated images on professional and consumer videotape recorders, project them on large screen projectors or televisions and transmit them across a videoconference link. Adjustments such as zoom and pan, picture positioning and

sizing, digital flicker filter, and underscan/overscan switching are accessible via a small handheld IR remote, RS232/242, or front panel keypad. Compatible with all platforms.

Fully broadcast compatible, enabling GenLock to a black burst signal with separately adjustable delay and subcarrier phase. All models convert unput from any computer to broadcast quality composite (NTSC/PAL) and S-VHS.

- Pro. Video Scan Converter (U.S.) . . . .1310-09097-002
- Pro. Video Scan Converter (Intl.) . . . .1310-09097-003

**Focus Enhancements TView Gold Scan Converter**



Offers unparalleled picture quality and maximum flexibility to meet the need of professionals around the globe. Utilizing FOCUS Enhancements proprietary TrueScale digital video processing, supports resolutions from VGA to XGA at frequencies up to 90 Hz. Uses TrueScale image compression

with independent horizontal and vertical underscan to fit images precisely onto any television without dropping lines or sacrificing picture clarity. Uses enhanced IniViewer monitor pass-through circuitry and includes zoom, freeze, and panning functions accessed through infrared remote.

- Consumer Video Scan Converter . . . . .1310-09097-001

**Adtran® NT-1 ACE**



Provides a (U) interface between your ViewStation and the ISDN network. The unit provides visible LED status indicators to aid in fault detection. Includes power supply and 6' telephone cable (RJ45 to RJ11).

- Adtran® NT-1 ACE . . . . .2200-08406-0

### Sprint® UT4620 Quad NT-1



A compact, versatile and affordable Network Termination Type 1 (NT-1) device that provides the link between the Integrated Services Digital Network (ISDN), Customer Premise Equipment (CPE) and Central Office (CO) switching equipment and supports up to 4 BRIs. Provides the func-

tionality of four NT-1 type devices and converts each U-Interface to a pair of S/T-Interfaces for full duplex operation of each BRI. Comes with a 16 watt AC power supply for use in Video Conferencing, Data Conferencing or low-power ISDN telephones.

Quad NT-1 . . . . . 2200-08406-004

### Sprint® NT3620 Triple NT-1



A compact, affordable device designed to provide a link between the Integrated Services Digital Network (ISDN), Customer Premise Equipment (CPE), and Central Office (CO) switching

equipment. Converts the two-wire "U" interface that comes from the telephone company to a four-wire S/T interface to provide ISDN telephones, terminal adaptors and video conferencing systems access to Basic Rate Interface (BRI) ISDN services and can handle up to 3 BRIs. Designed with 384 kbps video conferencing in mind, but can be used as a basic NT-1.

Triple NT-1 . . . . . 2200-08406-003

