

ViewStation Group Conferencing Products

| System Type | Product Placement | Differentiating Features | Max Data Rate (kbps) H.320 | Max Data Rate (kbps) H.323 | Network Interface | Upgrades Available | Monitor Support | Multipoint Capability |
|---------------------------|---|---|----------------------------|----------------------------|---|-----------------------------------|-----------------|--|
| ViewStation SP | Office or small conference rooms 1-3 people | Document Camera or VCR Playback Microphone head set (option) 1 LAN Port 1 Mic Pod only | 128 | 768 | ISDN Ethernet/LAN | N/A | 1 | N/A |
| ViewStation SP 384 | Office or small conference rooms 1-3 people | Document Camera or VCR Playback Microphone head set (option) 1 LAN Port 1 Mic Pod only | 384 | 768 | ISDN Ethernet/LAN | N/A | 1 | N/A |
| ViewStation 128 | Small to medium conference rooms 1-5 people | Document Camera & VCR Playback 2nd Mic Pod (optional) 2 Port LAN Hub Streaming supported | 128 | 768 | ISDN Ethernet/LAN | VS 512 VS MP | 2 | Quad BRI IMUX and software upgrade required for MP |
| ViewStation H.323 | Medium to large conference rooms 1-10 people | Document Camera & VCR 2nd Mid Pod (optional) 2 Port LAN Hub Streaming supported | Requires upgrade | 768 | Ethernet/LAN | VS 512 DCP VS V.35 VS MP | 2 | Software upgrade to MP required 4 @ 128 kbps 3 @ 256 kbps ISDN |
| ViewStation 512 | Medium to large conference rooms 1-10 people | Document Camera & VCR 2nd Mic Pod (optional) 2 Port LAN Hub Streaming supported | 512 | 768 | ISDN Ethernet/LAN | VS 512 DCP VS V.35 VS MP | 2 | Software upgrade to MP required 4 @ 128 kbps 3 @ 256 kbps ISDN |
| ViewStation MP | Medium to large conference rooms 1-10 people | On-Demand Multipoint capability Document Camera & VCR 2nd Mic Pod (optional) Streaming supported | 512 | 768 | ISDN Ethernet/LAN | N/A | 2 | 4 @ 128 kbps 3 @ 256 kbps ISDN |
| ViewStation DCP | Medium to large conference rooms 1-10 people | Document Camera & VCR 2nd Mic Pod (optional) 2 Port LAN Hub Streaming supported Supports Lucent® DEFINITY® ECS | 512 | 768 | Lucent DEFINITY ECS Ethernet/LAN | VS MP | 2 | Software upgrade to MP required 4 @ 128 kbps ISDN 3 @ 256 kbps ISDN via DCP ports |
| ViewStation V.35 | Medium to large conference rooms or classrooms 1-10 people | Document Camera & VCR 2nd Mic Pod (optional) Provides connection to T1/E1, ATM and VPN 2 Port LAN Hub Streaming supported | 768 | 768 | V.35/RS-449; direct connect or RS-366 dialing Ethernet/LAN | VS 512 VS MP | 2 | Quad BRI IMUX and software upgrade required for MP 4 @ 128 kbps ISDN 3 @ 256 kbps ISDN via DCP ports |
| ViewStation FX | Large conference rooms, boardrooms or classrooms 1-30+ people | TV quality video 2nd PTZ cameras RS 232 Dataport SXGA resolution graphics support Multipoint up to 4 @ 384 Streaming capabilities International POTS add-in | 2Mbps | 2Mbps | PRI V.35 Ethernet/LAN | N/A | 2 + (1 XGA) | 4 @ 384 kbps 3 @ 512 kbps via ISDN or LAN |
| VS4000 Codec | Custom integration 1-30+ people | TV quality video 2 External cameras Supports up to 4 monitors RS 232 Dataport SXGA resolution graphics support Multipoint up to 4 @ 384 Streaming capabilities On/off echo cancellor Dual Microphones Standard International POTS add-in | 2Mbps | 2Mbps | PRI V.35 Ethernet/LAN | N/A | 3 + (1 XGA) | 4 @ 384 kbps 3 @ 512 kbps ISDN or LAN |