

Suttle DSL Line Conditioners

630 Series Wall Mount Filter

Product Reference



Front




Back

Product Description

The Wall Mount DSL Adapter mounts to an existing wall mount phone jack providing an unfiltered jack for your DSL connection plus one or two filtered lines for voice device communications (e.g. phone, fax, answering machine, Caller ID box) via two auxiliary phone jacks. Used at each phone jack in use, Suttle wall mount DSL filters eliminate all erratic impedance from telephone equipment that can interfere with DSL communications.

Product Features

- * Customer installable, this adapter securely snaps over existing wall jack
- * Provides one or two filtered lines via two voice jacks and includes an auxiliary DSL Jack
- * Line 2 is pass through to all connections
- * Meets ANSI T1.421 standards for DSL filter compliance
- * FCC Registered; Complies with Part 68, FCC Rules



Ordering Information

Part Number

630LCCU-50

630LCCU-2F-50

Item Description

1 Line Filtered (pins 3 & 4), 2 voice jacks, Auxiliary DSL jack

2 Lines Filtered (pins 3 & 4, 2 & 5), 2 voice jacks, Auxiliary DSL jack

Packaging:

1 filter/bag; 20 bags/carton

Suttle DSL Line Conditioners

630 Series Wall Mount Filter

Product Specifications

- Filter Topology is 2-pole Low Pass
- REN = 0.1 (B)
- Loading capacity on telephone port is 15.5 nf



Electrical Characteristics

DC Loop Current Filter Meets Spec
Between 0 & 90mA DC

Stopband Attenuation
Off-Hook (min):
25 kHz-50 kHz 21 dB
50 kHz-12 MHz 25 dB

Off-Hook Insertion Loss
At 1 kHz 0.1 dB


Off-Hook Insertion Loss Distortion
200 Hz - 4 kHz ± 0.3 dB

Off-hook Impedance Distortion with ZHP

Phone Port:
ERL 17 dB
SRL-LO 25 dB
SRL-HI 9 dB
Network Port:
ERL 18 dB
SRL-LO 15 dB
SRL-HI 11 dB

Envelope Delay
300Hz to 2.8kHz <100 us

Dimensions



Specifications subject to change without notice. Revised 5/03.
© Suttle, a division of Communications Systems Inc. All Rights Reserved. 03-630LCCU