

GAI-TRONICS CORPORATION

ENCLOSURES



255

Weatherproof Enclosures

- Glass-reinforced polyester Enclosure
- Equipped with a #630 mounting plate to accommodate a standard wall telephone
- Weather-resistant design
- Suited for harsh outdoor use
- Also available with Spring return locking door, or hasp lock hardware for added security
- Can be pole mounted using GAI-Tronics Model 230 kit



236YL, 236RD, 236BK
Surface Mount Enclosures
 (shown with 276-001)

- Accommodates GAI-Tronics Flush-Mount Phones in custom recess
- Non-corrosive all aluminum construction
- Polyurethane Finish for enhanced durability
- Offered in OSHA Yellow (236YL), Safety Red (236RD), or standard Black (236BK)
- Telephone handset "Icon" label on side panels clearly indicates function to potential users
- Raised mounting bosses on rear for irregular surfaces
- USOC RJ11 connection terminal
- Can be pole-mounted using GAI-Tronics' Model 231 kit
- Custom colors and labeling available

Comparison Chart

	260/270 Series	351-001	255	236YL, 236RD, 236BK
Approvals	FCC registered, UL listed, DOC approved	FCC registered, DOC approved	Material: Glass-reinforced polyester	Material: .063 Aluminum with polyurethane finish; YL = Yellow, RD = Red, BK = Black
Hazardous Approvals	UL listed all hazardous areas CSA approved for Class I, Div. 1, Groups A, B, C, D; Class II, Div. 1, Group G (incl. coal dust); Class III, Div. 1	CSA approved for Class I, Div. 2, Groups A, B, C, D; Class II, Div. 2, Group G, (incl. coal dust); Class III	Supports Telephone Models: Most standard commercial wall mount telephones. Equipped with #630 mounting plate	Supports Telephone Models: Models - 276-001, 277-001, 297, and 298
Material	High-impact, glass reinforced polyester	High-impact, glass reinforced polyester	Mounting: Four .44" (11mm) mounting holes	Mounting: Four 5/16" (8mm) mounting holes
Operation	Loop Start	Loop Start	Dimensions: <u>Outside</u> 14.6(371)H x 10.9(277)W x 10.5(267)D; in (mm) <u>Inside</u> 11.5(292)H x 7.75(197)W x 8 (203)D; in(mm)	Dimensions: 12.3(312)H x 10.3(262)W x 6.37(162)D; in(mm)
Dialing	DTMF	DTMF	Weight: 6.5 lbs. (2.9kg)	Weight: 3.5 lbs. (1.6kg)
Handset Cord	6ft. Hytrel® standard	6ft. Hytrel® standard		
Ringer Equivalence	0.4B	0.8 B		
Minimum Loop Current	12 mA	21 mA		
Enclosure Rating	CSA listed NEMA 3; UL listed NEMA 3R	CSA listed NEMA 3		
Operating Temperature	-40°C (-40°F) to + 60°C (140°F)	-40°C (-40°F) to + 60°C (140°F)		
Power Supply	90-130VAC/180-240VAC 50/60Hz	Line Powered		
Relative Humidity	to 95%, non-condensing	to 95%, non-condensing		
Dimensions	262 - 9.5(242)H x 8(204)W x 3.9(98)D; in(mm) 272 - 13.2(334)H x 9.4(239)W x 7.4(188)D; in(mm) 263 - 13(330)H x 9.3(236)W x 3.9(98)D; in(mm)	13.2(334)H x 9.4(239)W x 7.4(188)D; in(mm)		
Weight	262 - 6 lbs. (2.7kg) 272 - 11.6 lbs. (5.3kg) 263 - 10 lbs. (4.5kg)	8.2 lbs. (3.72kg)		