

GAI-Tronics Corporation offers a full line of Industrial Telephone Enclosures to protect telecommunications equipment in very harsh environments. These enclosures are ideally suited for outdoor use, for areas with harsh or corrosive chemicals, or any environment where protective housing is required.

The enclosures are constructed of durable glass-reinforced polyester, resistant to weather and corrosive chemicals. The hinged door provides a positive seal when the door is closed and securely latched. All models are available with an optional locking door or hasp lock hardware for added security.

The Model 255-001 Weatherproof Enclosure is equipped with a mounting plate to accommodate a standard wall telephone.



**Model 255-001 Enclosure with
Modular Wall Telephone Jack**

Models Available

255-001 Enclosure with Modular Telephone Jack

Options Available (255-001)

CODE	DESCRIPTION
SK	Spring Door Return
LD	Keylock Door
HP	Hasp Lock Hardware

SPECIFICATIONS

Dimensions, outside	10.9(277)W x 14.6(371)H x 10.5(203)D; inches (mm)
Dimensions, inside	7.75(197)W x 11.5(292)H x 8(203)D; inches (mm)
Material	Glass-reinforced polyester
NEMA Rating	4X
Mounting	Four (4) 0.43 inch (11mm) diameter mounting holes
Weights	6.5 lbs. (2.94 kg)
Telephone Jack	RJ11



Model 232-001



Model 230-001

Model 231-001 and 232-001 utilize captive screw mounting holes to prevent unauthorized removal of equipment.



Model 231-001

GAI-Tronics Pole Mount brackets provide a suitable mounting surface for a variety of pole shapes. The universal bands are capable of securing the bracket to poles that are between 2.5 inches and 15 inches in diameter.

For additional support or for poles less than five inches in diameter, center mounting holes are provided for lag or machine bolts.

All pole mount brackets are manufactured using 14-gauge cold-rolled steel with a gray polyurethane finish. The banding straps are 0.012 inch x 0.5 inch stainless steel.

POLE MOUNT KIT GUIDE

GAI-Tronics Model	230-001	231-001	232-001
226-001 226-005 Rugged Industrial Telephone			•
227-001 227-005 Rugged Auto-dial Telephone			•
246-001 246-005 Industrial Telephone		•	
255-001 Enclosure	•		
256-001 256-005 Industrial Telephone (Weatherproof)	•		
261-001 Intrinsically-Safe Telephone		•	
271-001 Weatherproof Intrinsically-Safe Telephone	•		
393-00x RED ALERT® Emergency Telephone		•	
394AL-00x RED ALERT® Telephone		•	
351-001 Division II Telephone (Weatherproof)	•		
13353 / 13363 / 13373 Addressable Amplified Speaker		•	
XB001 Ling-Life Battery Enclosure	•		

Pub. 910100 Rev. 10/2011



GAI-Tronics® USA (Corporate) Toll Free: 1 (800) 492-1212 Tel: (610) 777-1374 Fax: (610) 796-5954 www.gai-tronics.com
GAI-Tronics® UK Tel: +44 (0)1283 500500 Fax: +44 (0)1283 500400 www.gai-tronics.co.uk
GAI-Tronics® S.r.l - Italy Tel: +39 02 4588801 Fax: +39 02 93663110 www.gai-tronics.it
GAI-Tronics® Malaysia Tel: +60-3-8945-4035 / 8945-7348 Fax: +60-3-8945-4675 www.gai-tronics.com
GAI-Tronics® Austdac - Australia Tel: 011-61-28-851-5000 Fax: 011-61-29-899-2490 www.austdac.com.au

Quality Management System Certified by DNV - ISO 9001:2008

The policy of GAI-Tronics is one of continuous improvement; therefore the company reserves the right to change specifications without notice.