



Series CH - Common Audible Control Units

Wheelock Series CA Common Audible Control Units monitor multiple analog telephone lines (tip and ring) to provide all call signaling, zoned signaling or night bell connection. These control units also enable connection for operation of external audible or visual alerts to be operated directly off the telephone ring voltage output.

Features

- Approvals Include: UL Listed
- Enables electronic key systems, PBX or 1A2 key systems to have a dry contact closure to trigger other devices
- Choice of two outputs for alert signal connection: standard ringing voltage or contact closure
- Easy connection to Wheelock's dry contact interface (DCI-24-24) or power supply (EPS-2401) for driving 24 volt alert signals.

CA-312-1 3 CO Line, 1 Control Unit

- Monitors 3 tip and ring lines, 1 zone

CA-622-1 6 CO Line, 2 Control Unit

- Monitors 6 tip and ring lines, up to 2 zones
- Additional units can be cascaded to monitor additional input lines



CA-312-1
CA-622-1

Specifications & Ordering Information

Model Number	Order Code	Application	Input Voltage	Output	REN
CA-312-1	3780	Monitor up to 3 Tip & Ring Lines, 1 Zone	55-130V, 20-30 Hz	Ringing Voltage or Dry Contact Closure	1
CA-622-1	3779	Monitor Up to 6 Tip & Ring Lines, 2 Zones			1

Series TB - Telbells

Features

- Aluminum bell housing
- Integral RFI suppression
- Screw terminal connections and RJ-11 plug

Series TB Modular Bells

- Approvals Include: TB-593 is UL Listed
- Motor Driven
- Tamper resistant volume control
- Applications: Telephone Ringers
- Weatherproof backbox for indoor/outdoor mounting included



TB Modular Bells

Specifications & Ordering Information

Model Number	Order Code	Shell Size	Input Voltage	Input Current	dBa @ 10 Feet
TB-591	4102	6"	38-60 VDC	0.025	100
TB-592	4101	6"	18-30 VAC/DC	0.025/.030	100
TB-593	4103	6"	55-130 V 20-30 Hz	N/A	95