

FEATURES:



# TECHNICAL SPECIFICATIONS

# SPEAKER ATTENUATOR MODEL S-560

AUTO TRANSFORMER TYPE
BRUSHED STAINLESS STEEL PLATE
10 POSITION SWITCH PLUS 0 "OFF"
WALL MOUNTABLE
COMBINATION 25/70 VOLT OPERATION
20 WATT POWER RATING AT 25/70 VOLTS



### **DESCRIPTION:**

The **S-560** permits changes to the audio level of speakers and horns without altering the speaker wiring connections. Tap the speaker for the maximum audio level required and use the attenuator to change the volume level. The attenuator features a stainless steel plate with embossed numbers and fits a single gang electrical wall box. The attenuator controls a 20 watt speaker load with a 10 position tap switch and operates on 25 or 70 volt speaker lines.

#### SPECIFICATIONS:

# TOTAL ATTENUATION:

36 dB

0 = "OFF" 1-2, 6 dB; 3-10, 3 dB, at 70 V

#### POWER RATING:

20 Watts

# HOUSING AND FINISH:

Brushed stainless steel single gang plate with raised number dial scale; skirted black knob and position indicator

#### LINE TRANSFORMER:

25/70 Volt input and output

# DIMENSIONS AND WEIGHT:

4.5" (11.43 cm) H x 2.75" (6.99 cm) W x 2.125" (5.4 cm) D

Weight: 1 lb (.454 kg)

#### MOUNTING:

The **S-560** can be mounted in wall or on surface using single gang electrical box.