

Accessories

PG-3 & PG-10A

Paging Amplifiers



PG-3



3 Watt Intercom Paging Amplifier:

- Compatible with LEF, LAF-C and NEM systems
- Does not require a separate paging adaptor
- \bullet 20 Ω and AUX inputs
- 2Ω and 8Ω outputs
- Built-in volume control
- 12V DC powered

SPECIFICATIONS:

Power Source: 12V DC Power Output: 3 Watts


Distortion: Less than 1% at 1,000Hz, 1 Watt output

Input 1: $10K\Omega$, 100mVInput 2: 20Ω , 600mV

Outputs: 2Ω and 8Ω

Dimensions (HxWxD): 4-1/16" x 2-1/4" x 1-3/8"

PG-10A



10 Watt Paging Amplifier:

- Used for background music on the NEM system (w/ NB-U)
- Compatible with any Aiphone system that supports paging
- · Can be used as a standard paging amplifier
- 25V and 70V outputs
- Circuit breaker helps protect against surges and shorts
- · Shelf or wall mounted

SPECIFICATIONS:

Power Source: 110V AC

Power Output: 10 Watt, 25V and 70V Balanced

Input: 100mV for rated output

Distortion: Less than 3% at 1,000Hz, rated output

Frequency Response: +/- 3db, 100 - 15,000 Hz

Power Consumption: 30 Watts

Dimensions (HxWxD): 9-11/16" x 3-1/16" x 6"

Aiphone Communication Systems • 1700 130th Ave. N.E. • Bellevue, WA 98005 (425) 455-0510 • FAX: (425) 455-0071 • (800) 692-0200 • www.aiphone.com



Accessories

PG-20C, PG-50C, PG-100C

Paging Amplifiers with Built-in Paging Adaptors



FEATURES

- Built-in paging adaptor (PD-1, PD-2, MC-A/A) for intercom integration
- Telephone / Microphone input, switchable
- Background music input with separate volume control
- Full range volume and tone controls
- Separate bass & treble controls
- Black anodized brushed aluminum finish with black ABS end panels
- Adjustable paging pre-tone
- Fully short circuit and overload protected
- NTRL/C certified (Complies with both UL & CSA standards)

PG-20C PG-50C PG-100C



SPECIFICATIONS:

Power Source: 110V AC

Power Output: PG-20C: 20 Watts; PG-50C: 50 Watts; PG-100C: 100 Watts

Output: 70V rms

Power Consumption: PG-20C: 48 Watts; PG-50C: 80 Watts; PG-100C: 176 Watts

Distortion:

Less than 1% at 1,000Hz, Rated Outputs
Inputs:

Tel/Mic: 600W Balanced; Music: 10K W
Sensitivity:

Tel: 150mV; Mic: 1mV; Music: 100mV
Dimensions:

7-1/2"H x 12-3/4"W x 3"D (all amplifiers)

Weight: PG-20C: 5.5 lbs; PG-50C: 6.6 lbs; PG-100C: 8.8 lbs