

The innovative design of the QuadCab™ Wall Mount Cabinet provides four distinct advantages:

Quick Installation:

Cornerstone hinging allows the QuadCab™ Wall Mount Cabinet to be installed quickly in easy to manage segments.

Unmatched Versatility:

Rear section easily configured for a wide variety of applications using a broad variety of accessories that quickly clip into place.

250 Pound Load Capacity:

Construction supports loading with minimum sag.

Durability:

Rugged construction and heavy duty locks and hinges provide long life and a secure environment.

SPECIFICATIONS

Material

- Rear section, top/bottom hinge plates, front door: 16 ga. CRS
- Center section: 14 ga. CRS
- 19" mounting angles: 11 ga. CRS
- Cornerstone hinges: aluminum permold 4BF
- Depth members: 11 ga. CRS
- Finish: powder coat black or office white
- 19" rack mounting width per EIA-310-D
- 19" rack-style rails tapped #12-24
- 250 lbs. load capacity
- Grounding provisions per TIA-607 (front door, body and rear
- Acrylic window tinted smoke gray
- 16" on center stud mounting
- Front door and rear locks both keyed alike with key #CH751
- 3/8" diameter wall anchors required







Raceway knockouts



Patented eccentric conduit knockouts eliminate extra conduit bends


Rails adjustable from front to rear



accepts 110 block, patch panels, switches and more

Rear section easily

Front door available in solid or smoked acrylic window styles



filter kits available

Heavy duty locking hardware for long life and maximum security



Structured cable routing between front and rear sections



Outside view

Cornerstone die-cast hinges:

- Quick disconnect for speedy installation
- Supports 2½ times load capacity of normal wall mount
- Can easily be hinged left or right



Weight Load vs. Cabinet Deflection								
Load	Lbs.	30	45	100	150	200	250	
Deflection	ln.	0.00	0.06	0.25	0.31	0.50	0.93	

NOTE: For best results, mount equipment to rack uprights or rest on shelves mounted to uprights. Deflection results shown above are typical, actual deflection may differ based on mounting conditions of cabinet to wall and weight distribution of equipment in cabinet.

ORDER INFORMATION



QuadC	ab W	all Mo	unt Ca	abinets								
Delivery:	1	Rear s	ection	with CH751	lock		1	Front	door with	n CH751 F	key lock	
	1	Center	sectio	n			2	Top/b	ottom fine	ger plates	i	
	2	19" mo	unting	angles			2	Corn	erstone di	e-cast hir	nges	
					Cata	alog l	No.		Catalog	No.	Catalog	g No.
					24"	Heig	ht		36" Heig	ht	48" He	ight
					12 F	Rack	Un	its	19 Rack	Units	26 Rac	k Units
Depth	Door	Style	Color		2 Re	ear Wa	all l	Jnits	4 Rear Wa	all Units	6 Rear	Wall Units
20"	Windo	ow	Black		HW	/24			HW36		HW48	
26"	Windo	ow	Black		HW	/242	6		HW362	6	HW48	26
36"	Windo	ow	Black		HW	/243	6		HW363	6	HW48	36
20"	Solid		Black		HW	/24S	;		HW36S		HW48	S
26"	Solid		Black		HW	/24S	26		HW36S	26	HW48	S26
36"	Solid		Black		HW	/24S	36		HW36S	36	HW48	S36
20"	Windo	ow	Office	white	HW	/24W	٧		HW36V	/	HW48	W
26"	Windo)W	Office	white	HW	/242	6W	1	HW362	6W	HW48	26W
36"	Windo	ow	Office	white	HW	/243	6W	1	HW363	6W	HW48	36W
20"	Solid		Office	white	HW	/24S	W		HW36S	W	HW48	SW
26"	Solid		Office	white	HW	/24S	26	W	HW36S	26W	HW48	S26W
36"	Solid		Office	white	HW	/24S	36	W	HW36S	36W	HW48	S36W



Lock Kit

Use to change key type to meet your application. Fits both QuadCab and REBOX®.

OuadCab Wall Maunt Cabi

Delivery: 1 Assembly lock and

Standard kit to replace existing locks

Catalog No. **CKL751**

Change key from CH751 to 333 Catalog No. **CKL333**

To convert to Bellcore 716 lock Catalog No. **CKL716**

To convert to European lock Catalog No. **CKLE**



Mobile Base Kit

Use to convert QuadCab™ Wall Mount Cabinet to floor standing cabinet.

Delivery: 1 mobile base, 4 swivel casters, 4 leveling feet, 1 cover for rear door

HWKMB Catalog No.



Gasket Kit

Use to enhance protection against dust and water, and performance of fan and filter kit

Delivery:

Adhesive-backed, foam gasket **HWKGT** Catalog No.



Fan Kit

Increases ventilation.

Delivery:

1 Fan tray assembly, wired 1 Kit mounting hardware 114 CFM, 120 VAC, 60 Hz

Catalog No. **HWKF120** 114 CFM, 230 VAC, 50 Hz

Catalog No. HWKF230 See page B24 for optional ther-

mostat kit.



Fan Filter Kit

Dust filter for air intake when using fans. Recommended use with gasket kit.

Delivery: Framed filters (1 kit required for 2' high cabinets, please use 2 kits for each 3' and 4' high cabinets)

HWKFF Catalog No.



Rear Rail Kit

Use to support the rear of deep heavy equipment.

Delivery: 2-19" mounting rails, 1 kit mounting hardware, 20 equipment mounting screws

	Catalog No.							
	Tapped	Square						
Height	#12-24	Holes M6						
24"	HWK241224	HWK6M6						
36"	HWK361224	HWK9M6						
48"	HWK481224	HWK12M6						



See pages B23-24 for more accessories.