

MAX® DUPLEX AND DESIGNER™ FACEPLATES



The MAX Duplex and Designer faceplates are designed for use with Simon's MAX series mounting frames. They are ideal for today's small office, home office, or residential environment. Faceplates include designation labels and color-matching label covers for circuit identification.



DP-S(XX) Single gang, plastic Duplex faceplate



DR-S(XX) Single gang, plastic Designer faceplate



DRE-D(XX) Double gang Designer/Duplex faceplate



DR-D(XX) Double gang Designer faceplate



RELATED PRODUCTS
MAX Modules pages 1.2 – 1.7

Use (XX) to specify color: 02 = white, 20 = ivory, 25 = bright white, 80 = light ivory

MAX MODULAR MOUNTING FRAMES



Simon's MAX mounting frames provide a solution for installing MAX modules in an environment where electrical Duplex or Designer style faceplates are desired. They can be used with any Duplex or Designer style faceplate.

DUPLEX MOUNTING FRAMES

MX-E2F(XX) Duplex mounting frame, accepts two flat MAX modules



MX-E2A(XX) Duplex mounting frame, accepts two angled MAX modules



MX-E4F(XX) Duplex mounting frame, accepts four flat MAX modules



MX-E4A(XX) Duplex mounting frame, accepts four angled MAX modules



DESIGNER MOUNTING FRAMES


MX-D1(XX) Designer mounting frame, accepts one flat or angled MAX module



MX-D2(XX) Designer mounting frame, accepts two flat or angled MAX modules



MX-D4(XX) Designer mounting frame, accepts four flat or angled MAX modules



MX-D6F(XX) Designer mounting frame, accepts six flat MAX modules



Use (XX) to specify color: 02 = white, 20 = ivory, 25 = bright white, 80 = light ivory

RELATED PRODUCTS HD15 Mounting Frame page 1.7

WALL PHONE FACEPLATES



WPJP Plastic Wall Phone Faceplate with 4-pair USOC jack included



MX-WP(XX)-SS MAX Series Stainless Steel Wall Phone Faceplate with keystone MAX module included



MX-WP-SS MAX Series Stainless Steel Wall Phone Faceplate for keystone MAX modules



Use (XX) to specify wiring option: C5 = 4-pair, category 5e, T568A/B; U3 = 3-pair, 6-position USOC; U4 = 4-pair, 8-position USOC