Work Area

ANGLED CT® 6 COUPLERS

PATENTED





Siemon's patented gravity-feed jack controls the bend radius of the mated modular cords to ensure the integrity of the transmission channel, while physically protecting the connection from incidental contact at the work area. This angled shroud creates a slim profile, perfect for installations in shallow raceways and modular furniture.

CT-C6-C6-(XX) Angled, double coupler, T568A/B wiring





Technical Tip!

Angled couplers are recommended for work area applications.

Use (XX) to specify color: 01 = black, 02 = white, 04 = gray, 20 = ivory, 80 = light ivory, 82 = alpine white Add "-D" for spring door option

RELATED PRODUCTS CT Faceplates page 1.21, Palm Guard page 12.7, MC° 6 Patch Cords page 4.3

FLAT CT 6 COUPLERS

PATENTED





Flat CT 6 couplers are designed for use in flush mount applications and are also recommended for use with CT patch panels.

CT-F-C6-C6-(XX) Flat, double coupler, T568A/B wiring



CT-F-C6-(XX) Flat, single coupler, T568A/B wiring



Technical Tip!

Flat couplers are recommended for patch panel applications.



Use (XX) to specify color: 01 = black, 02 = white, 04 = gray, 20 = ivory, 80 = light ivory, 82 = alpine white

Add "B" to end of part number for bulk project pack of 100 couplers

(Bulk option includes couplers and icons only — termination caps and cable ties are available separately see page 1.19).

Couplers include one color-matching icon (clear for black) and one termination cap per port, plus one red and one blue icon.

RELATED PRODUCTS CT Panels pages 2.8 – 2.10, Palm Guard page 12.7, MC* 6 Patch Cords page 4.3

Modular Patching

Racks and Cable Management

Modular Patch Cords and Components

Fiber

Industrial

Shielded/ Screened

S210 Products

S110 Products

S66 Products/ Protection

Residential

Tools and Testers

Web Resources

System Design Guide

Standards Update

Glossary

Index