

Product Information

Audio Conferencing Phone with Full Duplex Technology



Optional: Extension Microphones sold in pairs

Features

Digital Signal Processing

Full Duplex Technology

LCD Display

1 Year Warranty

Analog Line Connection

Omni-directional Microphone

Three Surround Speakers

User-friendly Menu System

Optional Extension Microphones

Advanced Audio Conferencing Solutions



The model PT-1205 Audio Conferencing Phone from Sprint offers advanced conferencing solutions with Full Duplex technology. This system, priced competitively with the industry's most popular models, is loaded with features found only in top-of-the-line conferencing units. Its quality, performance and price offer a new alternative which places you in an ever more competitive position to win your customers business.

The model PT-1205 Audio Conferencing Phone from Sprint with analog line connection is multifunctional for offices and conference rooms up to 300 square feet. Optional extension microphones are available for rooms up to 700 square feet.

With digital signal processing, an omni-directional microphone and three surround speakers, this Audio Conferencing Phone provides both high quality sound and voice transmission. Full Duplex conferencing allows echo-free conversations uninterrupted by annoying clipped voices.

This conferencing unit has a keypad with user-friendly menu system, phone book, flash button for multi-party calls, redial function, mute and volume control buttons. Its large, illuminated display offers easy visibility of date, time and duration of call. In addition, the display can be programmed for English, French or Spanish.



Audio Conferencing Phone with Full Duplex Technology

Technical Specifications

PT-1205

AC Transformer (USA):	120V AC/ 12 V DC; 700 mA
Network Interface:	Analog PBX or PSTN, RJ-11
Power Supply and Network Cable:	7.5 Meter, RJ-11 (line), EIAJ Class IV (power)
Recommended Room Conditions:	Reverberation Time < 0.5 sec. Background noise < 45 dB(A)
Frequency Response:	200–3700 Hz
Loudspeaker Volume:	85 dB SPL (increased if extension microphones are used)
Room Echo Suppression:	208 ms
Line Echo Suppression:	25 ms
Automatic Calibration:	< 1 ms impulse (not discernible)
Tape Recorder Output:	3.5mm jack
Dimensions:	Diameter 9.2 Inches
Weight:	< 2 Lbs.
Temperature Range:	40 – 104° F
Humidity:	20% - 80% non-condensing
Regulatory and Safety Approval:	FCC Part 15, Part 68 Industry Canada CS-03 ETL (US and Canada)

Extension Microphones (optional, sold in pairs)

Power Supply:	Power From Microphone Outlet
Cabling:	2x5 ft and 2x 8 ft, RJ-22
Microphone:	Omnidirectional
Microphone Indicator:	Green— Microphone On Red— Microphone Off

Ordering Information

Item #	Manf. #	Description
707600	PT-1205	Audio Conferencing Telephone with LCD Display
707605	PT-MICS	Pair of Extension Microphones for Audio Conferencing Telephone

To place an order or for more information, call **1-800-755-1950**
or visit us at www.sprintnorthsupply.com

Sprint Products Group
600 New Century Parkway
New Century, KS 66031-8000
913-791-7700
Fax 913-791-7022
www.sprintproductsgroup.com

Wholly Owned by Sprint North Supply

