

ULTRA™ MC® 6 MODULAR CORDS



Part #	Description
MC6-8-T(XX)-(XX)U	Ultra MC 6, double-ended, 4-pair stranded modular cord, T568A/B, color-matching jacket/boot

Use 1st (XX) to specify cord length: 03 = 0.9m (3 ft.), 05 = 1.5m (5 ft.), 07 = 2.1m (7 ft.), 10 = 3.1m (10 ft.), 15 = 4.6m (15 ft.), 20 = 6.1m (20 ft.)
 Use 2nd (XX) to specify color: 01 = black, 02 = white, 03 = red, 04 = gray, 05 = yellow, 06 = blue, 07=green
 ⓘ Add "B" for bulk project pack of 100 modular cords

RELATED PRODUCTS Ultra HD® 6 Patch Panels page 2.2 – 2.3,
 Ultra MAX® 6 Modules page 1.2 – 1.3

MC 6 MODULAR CORDS



Siemon's MC 6 modular cords are the key to unlocking the next generation performance of System 6® (MAX® 6, CT® 6, and HD® 6) products. MC 6 modular cords utilize patented, metallic isolator shields for optimum NEXT performance and a slide-on boot to ensure proper bend relief. All Siemon factory assembled MC 6 cords are 100% factory transmission tested to 250 MHz.



Part #	Description
MC6-8-T(XX)-(XX)	MC 6, double-ended, 4-pair stranded modular cord, T568A/B, color matching jacket/boot

Use 1st (XX) to specify cord length: 03 = 0.9m (3 ft.), 05 = 1.5m (5 ft.), 07 = 2.1m (7 ft.), 10 = 3.1m (10 ft.), 15 = 4.6m (15 ft.), 20 = 6.1m (20 ft.)
 Use 2nd (XX) to specify color:
 01 = black, 02 = white, 03 = red, 04 = gray, 05 = yellow, 06 = blue, 07=green
 ⓘ Add "B" for bulk project pack of 100 modular cords

Custom lengths are available upon request.
 Contact our Customer Service Department for more information.

Technical Tip!

Factory terminated and tested modular cords are required to achieve consistent category 5e or 6 channel performance. Field termination is not recommended.

SOLID IC6 SINGLE-ENDED MODULAR CORDS



Siemon's IC6 solid single-ended modular cords are designed for use in System 6 applications requiring a consolidation point (CP) or cross-connect (as an equipment cord). The IC6 cords are 100% factory transmission tested to 250 MHz and feature the same plug construction used in MC 6 modular cords. These cords are available in plenum and non-plenum versions and are single-ended for direct termination.



Part #	Description
IC6-8A-(XX)-B(XX)	IC6, single-ended, non-plenum, 4-pair solid modular cord, T568B, gray jacket with colored boot
IC6-8T-(XX)-B(XX)	IC6, single-ended, non-plenum, 4-pair solid modular cord, T568A, gray jacket with colored boot
IC6-8A-(XX)-B(XX)P	IC6, single-ended, plenum, 4-pair solid modular cord, T568B, blue plenum jacket with colored boot
IC6-8T-(XX)-B(XX)P	IC6, single-ended, plenum, 4-pair solid modular cord, T568A, blue plenum jacket with colored boot

Use 1st (XX) to specify cord length: 10 = 3.1m (10 ft.), 20 = 6.1m (20 ft.), 30 = 9.1m (30 ft.), 40 = 12.2m (40 ft.), 50 = 15.2m (50 ft.), 60 = 18.3m (60 ft.)
 Use 2nd (XX) to specify color of boot: 01 = black, 02 = white, 03 = red, 04 = gray, 05 = yellow, 06 = blue, 07 = green
 Custom lengths and jacket options are available upon request. Contact our Customer Service Department for more information.

