



16262-SG1  
in 80401-1

## DECORA<sup>®</sup> PLUS Receptacles

### Features & Benefits

- Durable thermoplastic face is available in an array of designer colors
- Receptacles have a locked-in mounting strap with a self-grounding clip† riveted to the strap
- Tamper-resistant receptacles are Hospital Grade and include a unique shutter mechanism that opens easily for the insertion of 2- or 3-prong plugs while preventing entry by other small objects into either outlet slot
- Isolated Ground receptacles are Hospital Grade (identified by an orange face or triangle on the face). They eliminate electromagnetic interference by providing a separate path to ground
- Back and side wiring terminals permit fast installation of up to #10 solid or stranded conductors
- Triple-wipe copper alloy contacts ensure maximum conductivity

† Self-grounding when installed in a properly grounded metal wallbox.

### DECORA PLUS RECEPTACLES Back and Side Wired NEMA 5-15R & 5-20R

(Basic Cat. No. denotes Mahogany device, except Isolated Ground devices—Basic Cat. No. denotes Orange device)

Description	Cat. No./Color* 15A/125V	Cat. No./Color* 20A/125V
	5-15R	5-20R
Hospital Grade, Duplex	16262-HG I, W, G, R (N/A in Mahogany)	16362-HG I, W, G, R
Hospital Grade, Tamper Resistant Duplex	16262-SG I, W, R	—
Hospital Grade, Isolated Ground Duplex	16262-IG B, I, W, G, R, E	16362-IG B, I, W, G, R, E
Industrial Grade, Duplex	16262 I, W, GY, E	16362 I, W, A, GY, E

### Back and Side Wired NEMA 6-15R & 6-20R

Description	Cat. No./Color* 15A/250V	Cat. No./Color* 20A/250V
	6-15R	6-20R
Hospital Grade, Duplex	16662-HG W (N/A in Mahogany)	16462-HG I, W (N/A in Mahogany)

### Testing & Code Compliance

- UL Listed (File #E-13399)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited Ten-Year Warranty

### Material Characteristics

Environmental: Flammability UL-94, V2 Rating  
Operating Temperature: -40°C to 60°C  
Maximum Continuous

### \*Color

Basic Cat. No. denotes Mahogany device (unless indicated) and Orange for Isolated Ground (-IG) Devices. Isolated Ground Receptacle is distinguished by an orange triangle on its face. For other color selections, add suffix to the catalog number as follows: Ivory (-I), White (-W), Almond (-A), Mahogany (for IG devices only, add -B), Red (-R), Gray (-G or -GY), Ebony Black (-E).

Dimensional drawings on page T2.

For more information regarding coordinating wallplates, colors, materials, single and multi-gang, refer to Wallplates, section D.

### WALLPLATES FOR ISOLATED GROUND DEVICES Engraved with "Isolated Ground"

Description	Cat. No.	Color*
Decora Receptacle Wallplate	80401-IG	Orange only

