

ST AND SC CONNECTORS

Sold by:



FOCUS

SC DUPLEX CONNECTORS

SC connectors have a duplexing clip, which allows each connector to be removed individually. In the event fiber polarity is reversed during termination, there's no need to discard the connector. Simply remove connectors from the clip and switch to correct the mistake, saving valuable installation time and money. The duplexing clip also speeds troubleshooting. In the event there's a fault with a single connection, an individual connector can be removed from the clip and re-terminated without disturbing the adjacent connector.

Multimode

- FC2-SC-MM-J** Duplex, jacketed fiber, one black boot and one beige boot
- FC2-SC-MM-B80** Duplex, buffered fiber, two beige boots
- FC2-SC-MM** Duplex, jacketed/buffered fiber, one black and one beige jacketed boot; two beige buffered boots

Singlemode

- FC2-SC-SM-J(XX)** Duplex, jacketed fiber
- FC2-SC-SM-B(XX)** Duplex, buffered fiber
- Use (XX) to specify boot color: 02 = white, 06 = blue
- ⓑ Add "-B" to the end of part number for bulk pack (50/box).



SC SIMPLEX CONNECTORS

SC simplex connectors employ an outer housing that is color-coded in accordance with TIA/EIA-568-B.3 and ISO/IEC 11801 Ed2.0 requirements (beige for multimode and blue for singlemode).

Multimode

- FC1-SC-MM-J80** Simplex, jacketed fiber, beige boot
- FC1-SC-MM-J01** Simplex, jacketed fiber, black boot
- FC1-SC-MM-B80** Simplex, buffered fiber, beige boot
- FC1-SC-MM-01** Simplex, jacketed/buffered fibers, one black jacketed boot and one beige buffered boot
- FC1-SC-MM-80** Simplex, jacketed/buffered fiber, one beige jacketed boot and one beige buffered boot

Singlemode

- FC1-SC-SM-J(XX)** Simplex, jacketed fiber
- FC1-SC-SM-B(XX)** Simplex, buffered fiber
- FC1-SC-SM-(XX)** Simplex, jacketed/buffered fibers, one jacketed boots, one buffered boots
- Use (XX) to specify boot color: 02 = white, 06 = blue
- ⓑ Add "-B" to the end of part number for bulk pack (100/box).

ST CONNECTORS

The ST connector employs a rugged metal bayonet coupling ring with radial ramps which facilitate engagement to the studs of the mating adapter. Two ST connectors are available for jacketed fiber, one with a beige boot and one with a black boot. The two colors enable easy identification of the fibers when terminating individual connectors to form a duplex jumper.

Multimode

- FC1-SA-MM-J80** Jacketed fiber, beige boot
- FC1-SA-MM-J01** Jacketed fiber, black boot
- FC1-SA-MM-B80** Buffered fiber, beige boot
- FC1-SA-MM-01** Jacketed/Buffered fiber, black jacketed boot and beige buffered boot
- FC1-SA-MM-80** Jacketed/Buffered fiber, beige jacketed boot and beige buffered boot

Singlemode

- FC1-SA-SM-J(XX)** Jacketed fiber
- FC1-SA-SM-B(XX)** Buffered fiber
- FC1-SA-SM-(XX)** Jacketed/Buffered fiber, one jacketed boot, one buffered boot

- Use (XX) to specify boot color: 02 = white, 06 = blue
- ⓑ Add "-B" to the end of part number for bulk pack (100/box).



Work Area

Modular Patching

Racks and Cable Management

Modular Patch Cords and Components

Fiber

Industrial

Shielded/Screened

S210 Products

S110 Products

S66 Products/Protection

Residential

Tools and Testers

Web Resources

System Design Guide

Standards Update

Glossary

Index