



**Model 255 Enclosure with
Modular Wall Phone Jack**

GAI-Tronics Corporation offers a full line of Industrial Telephone Enclosures to protect telecommunications equipment in harsh environments. These enclosures are ideally suited for outdoor use, for areas with harsh or corrosive chemicals, or any environment where protective housing is required.

The enclosures are constructed of durable glass-reinforced polyester, resistant to weather and corrosive chemicals. The hinged door provides a positive seal when the door is closed and securely latched. All models are available with an optional locking door or hasp lock hardware for added security.

The Model 255 Weatherproof Enclosure is equipped with a #630A mounting plate to accommodate a standard wall telephone.

Models Available

255 Enclosure with 630A Phone Jack

Options Available (255)

CODE	DESCRIPTION
SK	Spring Door Return
LD	Keylock Door
HP	Hasp Lock Hardware

SPECIFICATIONS

Dimensions, outside: 10.9(277)W x 14.6(371)H x 10.5(203)D; inches (mm)
 Dimensions, inside: 7.75(197)W x 11.5(292)H x 8(203)D; inches (mm)
 Material: Glass-reinforced polyester
 Mounting: Four (4) 0.43 inch (11mm) diameter mounting holes
 Weights: 6.5 lbs. (2.94 kg)


Sold by:

Industrial Telephone Enclosures & Pole Mounting Kits

MODEL 230, 231 and 232



Model 232



Model 230

Model 231 and 232
utilize captive screw
mounting holes to
prevent unauthorized
removal of equipment.



Model 231

GAI-Tronics Pole Mount brackets provide a suitable mounting surface for a variety of pole shapes. The universal bands are capable of securing the bracket to poles that are between 2.5 inches and 15 inches in diameter.

For additional support or for poles less than five inches in diameter, center mounting holes are provided for lag or machine bolts.

All pole mount brackets are manufactured using 14-gauge cold-rolled steel with a gray polyurethane finish. The banding straps are 0.012 inch x 0.5 inch stainless steel.

POLE MOUNT KIT GUIDE

GAI-Tronics Model	230	231	232
226C Super-Rugged Industrial Telephone			•
227 Super-Rugged Autodial Telephone			•
246C Rugged Industrial Telephone		•	
255 Enclosure with #630A Mounting Plate	•		
256C Rugged Industrial Telephone (Weatherproof)	•		
261 Intrinsically-Safe Telephone		•	
271 Weatherproof Intrinsically-Safe Telephone	•		
293 Enhanced Emergency Telephone		•	
294AL Combination Telephone		•	
351 Division II Telephone (Weatherproof)	•		

Americas Division

GAI-Tronics Corporation, USA, Phone: 1-800-492-1212, 610-777-1374, Fax: (610) 796-5954,
www.gai-tronics.com ISO9001 Registered Company

European Division

GAI-Tronics Limited, UK, Tel: +44 1283 500500, Fax: +44 1283 500400,
www.gai-tronics.co.uk
 GAI-Tronics S.r.l, Italy, Tel: +39 02 48601 460, Fax: +39 02 4585 625

Asia Division

GAI-Tronics Corporation, Malaysia, Tel: +60 3 6277 6091, Fax: +60 3 6277 6093