

DHC Powerline Carrier Wall Switches with One-Button Programming

Scene-Capable Receiver with One-Button Programming — The new DHC Scene-Capable Receivers provide one-button programming for scene and address capturing. All feature Leviton's exclusive Intellisense® to ensure top performance and reliability even when noise is present on the AC powerline.

Dimming Wall Switch Receivers provide manual and remote ON/OFF switching and full-range dimming for incandescent and magnetic low-voltage lighting loads. The new HCS08-1TW Electronic Switch Receiver (non-dimming) provides manual and remote ON/OFF switching for incandescent, magnetic low-voltage, fluorescent and compact fluorescent lighting. The new HCP03-10W Plug-In Module allows remote ON/OFF switching and full-range dimming for freestanding lamps, incorporating them into the lighting scenes. All Switch Receivers come with a locator LED. Dimming models feature an LED brightness level display and a preset feature that turns lights ON at the last selected brightness level. Double Tap feature immediately adjusts light to full brightness without affecting the last selected brightness level. All -T Receivers allow 2-way status tracking with the DHC Toscana™ Deluxe Programmer and new 2-way capable controllers when receivers are changed locally.

Typical applications include home theaters, dining rooms, chandeliers, living rooms with multiple high-hats, entranceways, and a wide range of mood lighting applications.

| DESCRIPTION | CAT. NO. | RATING | COLOR |
|--|-----------|--|----------------------------|
| 600 Watt Scene-Capable Dimming Wall Switch Receiver with One-Button Programming and LED brightness display | HCM06-1DW | 600W, 125V AC Incandescent, 600VA (450W) Magnetic Low-Voltage Lighting | White (Ivory kit included) |
| 1000 Watt Scene-Capable Dimming Wall Switch Receiver with One-Button Programming and LED brightness display | HCM10-1DW | 1000W, 125V AC Incandescent, 1000VA (750W) Magnetic Low-Voltage Lighting | White (Ivory kit included) |
| 600 Watt Scene-Capable Dimming Wall Switch Receiver with One-Button Programming, 2-Way Communication and LED brightness display. Neutral connection required | HCM06-1TW | 600W, 125V AC Incandescent, 600VA (450W) Magnetic Low-Voltage Lighting | White (Ivory kit included) |
| 1000 Watt Scene-Capable Dimming Wall Switch Receiver with One-Button Programming, 2-Way Communication and LED brightness display. Neutral connection required | HCM10-1TW | 1000W, 125V AC Incandescent, 1000VA (750W) Magnetic Low-Voltage Lighting | White (Ivory kit included) |
| 1000W/1000VA 8 Amp Scene-Capable Electronic Switch Receiver (non-dimming) with One-Button Programming and 2-Way Communication. Neutral connection required | HCS08-1TW | 8 Amp, 125V AC 1000W Incandescent, 1000VA (750W) Fluorescent & Magnetic Low-Voltage Lighting | White (Ivory kit included) |
| 300 Watt Scene-Capable Dimming Plug-In Lamp Module with One-Button Programming | HCP03-10W | 300W, 125V AC Incandescent | White Only |

All devices are UL Listed and CSA Certified.

Special Note: As with any dimmer, derating for multiple gang installations is required for Wall Switch Receivers.

Use Leviton Power Extenders to extend the load capacity of DHC Dimming Wall Switch Receivers. Leviton Power Extenders are available for incandescent, magnetic low-voltage, electronic low-voltage, Advance Mark X™ fluorescent dimming ballasts or equivalents, and 0-10 VDC dimmable fluorescent ballasts such as Advance Mark VII™, OSRAM Sylvania Quicktronic® Helios™ or equivalent ballasts.

Note: A Cat. No. HCA02-10E System Amplifier must be installed at the main panel in every DHC installation to ensure adequate signal strength.

COLOR CHANGE KITS FOR WALL SWITCH RECEIVERS (ROCKER AND FRAME)

| For Receiver: | Compatible Color Change Kit | | | | | |
|---------------|-----------------------------|----------------|----------------|---------------|-----------------|----------------|
| | Cat. No. Mahogany | Cat. No. Ivory | Cat. No. White | Cat. No. Gray | Cat. No. Almond | Cat. No. Black |
| HCM06/10-1SW | — | DRK0D-1LI | DRK0D-1LW | DRK0D-1LG | DRK0D-1LA | DRK0D-1LE |
| HCM06/10-1DW | — | DRKDD-1LI | DRKDD-1LW | DRKDD-1LG | DRKDD-1LA | DRKDD-1LE |
| HCM06/10-1TW | — | DRKDD-1LI | DRKDD-1LW | DRKDD-1LG | DRKDD-1LA | DRKDD-1LE |
| HCS08-1TW | — | DRK0D-1LI | DRK0D-1LW | DRK0D-1LG | DRK0D-1LA | DRK0D-1LE |
| HCS10-1SW | — | DRK0S-1LI | DRK0S-1LW | DRK0S-1LG | DRK0S-1LA | DRK0S-1LE |

SPECIFICATIONS & FEATURES

- New One Button Programming
- Provide Scene Control capability when used with DHC Scene Controller HCCS7-1TW and HCCPG-1TW Toscana Programmer. Also backward compatible with 16400/16450-S and 16400/16450-SD Scene Controllers
- Receivers provide multi-station manual and remote On/Off switching and full-range dimming. Use MSOOR-10 Multi-Remote Unit (wall switch SW and DW suffix ONLY)
- Soft On/Fade Off brightness levels allowing extended bulb life
- Memory of last scene eliminating readjust settings — (HCS08-1TW and HCS10-1SW provide On/Off switch ONLY)
- Fits in standard wall boxes
- All devices come with Intellisense® technology providing the utmost in reliability
- Protected memory during minor power fluctuations
- LED locator light alongside rocker for convenience — on DW or TW suffix
- Packed with Ivory and White snap-on rocker/frame kit; optional snap-on rocker/frame color change kits sold separately. See color change kit chart

TESTING & CODE COMPLIANCE

- UL Listed to File No. E31373
- CSA Certified to File No. LR3413
- NOM Certified #057

COLOR

Colors available as indicated. See chart for Rocker and Frame Kits (must be purchased separately)

MATERIAL CHARACTERISTICS

Environmental: Flammability (Engineering Thermoplastic) UL-94, V-2 Rating
Operating Temperature: -40°C to 120°C

