

Power Devices

20 AMP 120/208V 3ØY 4-Pole 4-Wire

DESCRIPTION	CAT. NO.	WALLPLATE INFORMATION
Flush Mount Receptacle★	7250-FR	Fits any standard single gang receptacle plate. See Section G for more information.
	18-20R	
Matching Plug★	7251-C	
	18-20P	

30 AMP 125V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	WALLPLATE INFORMATION
Flush Mount Receptacle	5371†	Fits all wallplates with 2.15" diameter center hole. See Section G for more information
	5-30R	
Flush Mount Receptacle Isolated Ground	5371-IG	As above
Matching Angle Plug	9530-P	
	5-30P	

30 AMP 125V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.
Flush Mount Receptacle for Recreational Vehicles	7313
	TT-30R
Matching Angle Plug	830-T
	TT-30P ANSI STD. C73.13

†Matching single-gang wallplate: Cat. No. 84028. Matching Industrial Weather-Resistant cover: Cat. No. WP2.

All devices are UL Listed. Also CSA Certified except where indicated by★

*Matching single-gang plastic wallplate: Cat. No. 80525.



SPECIFICATIONS & FEATURES

- Heavy-gauge, double-wipe copper alloy contacts
- Easy-to-wire terminals accept up to No. 4 AWG conductors
- Terminals marked for easy identification and fast wiring
- All mounting hardware included
- Flush-mount devices fit single or two-gang outlet boxes

TESTING & CODE COMPLIANCE

- UL Listed for copper or aluminum conductors—except Cat. Nos. 7250, 7313, 830-T (File #E-13399); Angle Plugs (File #E-13393)
- UL Test 498
- CSA Certified for copper or aluminum conductors (File #152105); Receptacle for Recreational Vehicles (File #2781); CSA Test 42
- NOM Certified (#057)
- Meets NEMA and ANSI standards
- Backed by a Limited 10-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2
Operating Temperature: From -40° C (without impact) to 60°C maximum continuous

