




# 15A 125V & 20A 125V

## Commercial Grade, GFCI's

**2 YEAR LIMITED WARRANTY**



ELECTRICAL		
DIELECTRIC VOLTAGE	CURRENT INTERRUPT.	TEMP. RISE
Withstands 1500V per UL 498	10kA	30°C max at full rated current after 50 cycles overload at 150% rated current for both AC and DC per UL 498
<b>TRIP LEVEL</b>		
5±1 mA		

MECHANICAL		
TERMINAL I.D.	TERMINAL ACCOMMODATION	PRODUCT I.D.
Brass, hot Grounding Silver, neutral	#18- #12 AWG	Ratings permanently marked on device
ENVIRONMENTAL		
FLAMMABILITY	OPERATING TEMP.	
Rated V-2 per UL 94	-35°C to 66°C	

STANDARDS & CERTIFICATIONS					
NEMA WD-6	ANSI C-73	UL 943 Class A & 498	UL Fed Spec Listed WC-596	CSA C22.2	NOM
✓	✓	✓	-	#LR-57811	#057
AC HORSEPOWER RATINGS					
1.5					



### Right Angle GFCI Plugs **UL** Recognized Component

PLUG COLOR	ANGLE PLUG		ANGLE PLUG	
	AUTOMATIC RESET	MANUAL RESET	AUTOMATIC RESET	MANUAL RESET
	<b>15A 125V, NEMA 5-15P</b>		<b>20A 125V, NEMA 5-20P</b>	
Gray	6593	-	6893	-
Yellow	-	6594	-	6894

### Right Angle Plugs Accessory

COLOR	WATERPROOF COVER WITH GROUND PIN UP ORIENTATION
Clear	86593



20A 125V PANEL MOUNT GFCI w/ 16" LEADS & LED LIGHT YELLOW LEXAN
36596
PANEL MOUNT FOR TEMPORARY POWER DISTRIBUTION BOXES
36597



### High Current GFCI

Contact Rating: 20A 125V AC  
 Load Capability with 125V Control Relay  
 80@240V AC Max.

TOGGLE COLOR	BLANK FACE RESET BUTTONS
Ivory	8895-80I
White	8895-80W
Black	8895-80E

**UL** Recognized Component

**UL** Recognized Component



### GFCI-Protected Fluorescent Work Light w/Receptacle 13A 125V, 2-P 3-W Grounding

LENGTH	GFCI CORD SET, YELLOW CORD, 16/3 SJTW BLACK BODY, ON/OFF POWER SWITCH, 13 WATT LAMP & RECEPTACLE	NEMA PLUG	NEMA CONNECTOR
20'	66591-WL	5-15P	5-15R

