

# Leviton's New Portable Power Supply Cord Sets, Hand-Held Work Light Cord Set and Portable Power Distribution Centers

## Definition:

Leviton's in-line GFCI and premium grade cord set packages are available in 15 and 20 amp NEMA straight-blade and locking configurations. All devices are assembled in Leviton's cord set assembly plant and fully tested for quality assurance. Each device is Underwriters Laboratories and Canadian Standards Association listed as specified.

Industrial Black & White™ and Wetguard™ cord sets feature SOOW American Mustang™ cable. Every device is designed and manufactured to lessen downtime, reduce frequency of cord replacement and provide a safe working environment.

## Key features of SOOW Mustang™ cable include:







- UL, CSA, MSHA listed and OSHA approved
- Resistant to tears, cuts and abrasions
- Resistant to chemicals, acids, ozone, fungus and aging
- Resistant to flame and heat
- Water-submersible per UL/CSA requirements
- Extra durable and flexible



Cord Set Type	Lengths Available (In Feet)								Cord Type	Connection Type	Applications			
	2	3	6	25	35	37	50	100			Construction Site	In-Plant	Outdoor/Washdown	Health Care
In-Line GFCI Auto Reset	✓	✓	✓	✓	✓	✓			14/3 SJT Yellow Jacket	Molded-on plugs and connectors	✓	✓	✓	✓
In-Line GFCI Manual Reset		✓		✓					14/3 SJT Yellow Jacket	Molded-on plugs and connectors	✓	✓	✓	✓
In-Line GFCI With Work Light	Available in 20 ft. length only								16/3 SJTW Yellow Jacket	Molded-on plug	✓	✓	✓	✓
Black & White™ Cord Set				✓			✓	✓	12/3 and 14/3 SOOW Yellow "Mustang" Jacket	Industrial Black & White™ plug and connector	✓	✓		✓
Wetguard Cord Set				✓			✓	✓	12/3 and 14/3 SOOW Yellow "Mustang" Jacket	Wetguard™ plug and connector	✓	✓	✓	✓
Hospital Cordset				✓					12/3 SEOW Black	Hospital Grade, Power Light™ plug and connector				✓

# CORD SETS







## Industrial Grade, Black & White™ Straight Blade Cord Sets 15A 125V, 2-P 3-W Grounding

Length (In Feet)	14/3 SOOW Yellow Cord	12/3 SOOW Yellow Cord	NEMA Plug	NEMA Connector
25'	I515-43A	I515-23A	 5-15P	 5-15R
50'	I515-43B	I515-23B	 5-15P	 5-15R
100'	I515-43C	I515-23C	 5-15P	 5-15R



IL515-43A



## Industrial Grade, Black & White™ Locking Cord Sets 15A 125V, 2-P 3-W Grounding

Length (In Feet)	14/3 SOOW Yellow Cord	12/3 SOOW Yellow Cord	NEMA Plug	NEMA Connector
25'	IL515-43A	IL515-23A	 L5-15P	 L5-15R
50'	IL515-43B	IL515-23B	 L5-15P	 L5-15R
100'	IL515-43C	IL515-23C	 L5-15P	 L5-15R



HGPLC-25







## Hospital Grade Straight Blade Cord Set 15A 125V, 2-P 3-W Grounding

Length (In Feet)	12/3 SEOW Black Cord Lighted Transparent Device	NEMA Plug	NEMA Connector
25'	HGPLC-25	 5-15P	 5-15R



W515-43A

## Industrial Grade, Wetguard™ Straight Blade Cord Sets 15A 125V, 2-P 3-W Grounding

Length (In Feet)	14/3 SOOW Yellow Cord	12/3 SOOW Yellow Cord	NEMA Plug	NEMA Connector
25'	W515-43A	W515-23A	 5-15P	 5-15R
50'	W515-43B	W515-23B	 5-15P	 5-15R
100'	W515-43C	W515-23C	 5-15P	 5-15R

## Wetguard Cord Set Specifications & Features:

### General

- Sunlight, water and weather resistant per UL and CSA
- Resistant to oil, acid, impact, abrasion, water, flame and high temperature
- Passes MSHA flame test (P-136-MSHA)
- Maintains flexibility
- Suitable for continuous submersion in water
- Designed for extra hard usage with industrial equipment
- Synthetic Rubber Insulation
- SOOW can also be used for special applications as outlined in NFPA70 (N.E.C.) paragraph 501.4(b) CL.1 Div. 2 locations and paragraph 501.11 CL.1 Div. 2. Green grounding conductor required.
- ICEA where applicable







### Mechanical

- Color Coding: 3 Conductor Black, White & Green
- Conductors: Bare, annealed copper per ASTM B-3 Flexible, bunch-stranded per UL-62 sizes 18-8AWG Rope Lay sizes 6-2AWG
- Jacket: Oil-resistant

### Standards & Certifications



















- OSHA acceptable
- UL Listed: #E7362
- CSA: #LL-8825

## Industrial Grade, Wetguard™ Locking Cord Sets 15A 125V, 2-P 3-W Grounding

Length (In Feet)	14/3 SOOW Yellow Cord	12/3 SOOW Yellow Cord	NEMA Plug	NEMA Connector
25'	WL515-43A	WL515-23A	 L5-15P	 L5-15R
50'	WL515-43B	WL515-23B	 L5-15P	 L5-15R
100'	WL515-43C	WL515-23C	 L5-15P	 L5-15R



## GFCI-Protected Automatic Reset & Manual Reset Straight Blade & Locking Cord Sets

Length (In Feet)	GFCI Cord Set <b>Automatic Reset</b> Yellow Cord, 14/3 SJT Black Body Black Plug & Connector	GFCI Cord Set <b>Manual Reset</b> Yellow Cord, 14/3 SJT Yellow Body Yellow Plug & Connector	NEMA Plug	NEMA Connector
<b>15A 125V, Cord Sets</b>				
2' 3' 6' 25'	66591-2C — 66591-6C 66591-25C	— 69591-3 — 69591-25C	 5-15P	 5-15R
<b>15A 125V, Cord Set w/Triple Outlet</b>				
3'	66593-3	69593-3	 5-15P	 5-15R
<b>15A 125V, Locking Cord Set</b>				
3'	66597-3	—	 L5-15P	 L5-15R
<b>15A 125V, Cord Sets w/Wetguard™ Plug &amp; Connector</b>				
3' 25'	— —	69591-W3 69591-W25	 5-15P	 5-15R
<b>15A 125V, Power Supply Cord</b>				
37'	26591-37C	—	 5-15P	None
<b>15A 240V, Power Supply Cord</b>				
35'	26592-E	—	 6-15P	None
<b>20A 125V, Cord Set</b>				
3'	66891-3	69891-3	 5-20P	 5-20R
<b>20A 125V Cord Set w/Wetguard™ Plug &amp; Connector</b>				
3'	—	69891-W3	 5-20P	 5-20R
<b>20A 125V, Locking Cord Set</b>				
3'	66897-3	—	 L5-20P	 L5-20R
<b>20A 125V, Power Supply Cord</b>				
37'	36591-37C	—	 5-20P	None
<b>20A 125V, Power Supply Cord</b>				
35'	36592-E	—	 6-20P	None



69891-3



66593-3



66591-2C



69591-W3





69891-3



66591-WL





## GFCI-Protected Fluorescent Work Light w/Receptacle 13A 125V, 2-P 3-W Grounding

Length	GFCI Cord Set Yellow Cord, 16/3 SJTW Black Body On/Off Power Switch, 13 Watt Lamp & Receptacle	NEMA Plug	NEMA Connector
20'	66591-WL	 5-15P	 5-15R







# GFCI-Protected Power Distribution Center "The Box" & Power Cords

**Power Distribution Box – Locking Receptacles**  
**6 GFCI-Protected 20A/125V, Locking Receptacles**  
**1 GFCI-Protected 30A/250V, Locking Receptacle**  
**50A 125/250V Non-NEMA Power Connections**

Yellow Power Distribution Box Cat. No.	Power Inlet	Power Outlet	6 NEMA GFCI-Protected Receptacles	1 NEMA GFCI-Protected Receptacles
PB101-SGF	50A 125/250V Non-NEMA 	50A 125/250V Non-NEMA 	NEMA L5-20R 	NEMA L6-30R 



**Power Distribution Box – Straight/Locking Receptacles**  
**6 GFCI-Protected 20A/125V, Straight-Blade Receptacles**  
**1 GFCI-Protected 30A/250V, Locking Receptacle**  
**50A 125/250V Non-NEMA Power Connections**



Yellow Power Distribution Box Cat. No.	Power Inlet	Power Outlet	6 NEMA GFCI-Protected Receptacles	1 NEMA GFCI-Protected Receptacles
PB103-SGF	50A 125/250V Non-NEMA 	50A 125/250V Non-NEMA 	NEMA 5-20R 	NEMA L6-30R 

## THE BOX: Features and Benefits

### General

- Meets OSHA Regulation 20, Part 1926, Subpart K standards for open-neutral GFCI protection and circuit overload protection
- UL Listed for outdoor use
- Weatherproof covers prevent nuisance tripping; prevent moisture from entering contacts
- Available in 20 Amp straight-blade or 20 Amp locking versions
- Features one 50 Amp 125/250 volt supply inlet and one 50 Amp 125/250 volt outlet for feed-through applications; also includes one 30 Amp 250 volt locking receptacle
- Offers clear porthole panel for easy viewing of circuit breakers
- Individual circuit breakers offer overload protection to 20 Amp receptacles
- Sturdy reinforced metal housing and legs withstand abuse
- Available in high visibility yellow
- Backed by Leviton's One Year Limited Warranty

## Power Cables Flexible, Abrasion-Resistant Construction

Length	Black Flexible Cord with (3) #6 AWG and (1) #8 AWG Conductors Cat. No.	Yellow & White Weather-Resistant Plug	Yellow & White Weather-Resistant Connector
50' 100'	KRS-A9519 KUS-A9519	50A 125/250V Non-NEMA 	50A 125/250V Non-NEMA 



## Power Cable Features

### General

- Features flexible, abrasion-resistant construction offering reliable performance to -31° F
- 50 Amp 125/250 VAC weather resistant plug and connector

### Standards and Certifications:

UL Listed to File Number E-48380

**Leviton Manufacturing Co., Inc.**  
 59-25 Little Neck Parkway, Little Neck, NY 11362-2591  
 Telephone: 1-800-323-8920 • FAX: 1-800-832-9538  
 Tech Line (8:30AM-6:00PM Eastern Time Monday-Friday): 1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**  
 165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9  
 Outside Canada: 1-514-954-1840 • FAX: 1-514-954-1853/1854  
 Inside Canada: 1-800-469-7890 • Tech Line: 1-800-405-5320 • FAX: 1-800-563-1853

For more information, visit Leviton's website at [www.leviton.com](http://www.leviton.com)

