

## Porcelain Mogul Base Lampholders

With Leads\*

DESCRIPTION	CAT. NO.	RATING	OUTSIDE DIAMETER	OVERALL HEIGHT
Keyless, Single Circuit. For high pressure sodium lamps up to 1000 watts. 8-32 Mounting Screws on 1 $\frac{3}{8}$ " Centers	8746	1500W 600V 5KV Pulse-rated	2 $\frac{1}{8}$ "	3 $\frac{1}{64}$ "
Keyless, Single Circuit. Position-oriented. For Super Metalarc HID lamps. 8-32 Mounting Screws on 1 $\frac{3}{8}$ " Centers	8750	1500W 600V	2 $\frac{5}{32}$ "	2 $\frac{39}{64}$ "
Keyless, Single Circuit. For high-pressure sodium lamps up to 400 watts. 8-32 Mounting Screws on 1 $\frac{3}{8}$ " Centers	8756	1500W 600V 4KV Pulse-rated	2 $\frac{5}{32}$ "	2 $\frac{39}{64}$ "
Low Pressure Sodium. For use with all single-end bayonet base low pressure sodium lamps★	8806	660W 1000V	1 $\frac{3}{8}$ "	1 $\frac{5}{8}$ "

\*Leads types, lengths and ratings vary with the end use applications. Standard leads as well as variations available on inquiry.

### Screw Terminals

DESCRIPTION	CAT. NO.	RATING	OUTSIDE DIAMETER	OVERALL HEIGHT
Keyless; 2-Piece; Single-Pole★	8765	1500W 600V	2 $\frac{1}{4}$ "	2 $\frac{23}{64}$ "
Keyless; Single Circuit with 8-32 Lock Nuts on 1 $\frac{3}{8}$ " Centers. Die-cast caps available upon request	8694	1500W 600V	2 $\frac{5}{32}$ "	2 $\frac{11}{16}$ "

All devices are UL Listed. Also CSA Certified except where indicated by★



8756



8806

### SPECIFICATIONS & FEATURES

- Cat. No. 8746 – Porcelain body gray glazed with ceramic arc shield; Cat. No. 8750 – Porcelain body yellow glazed
- All other moguls listed have white glazed porcelain body
- Copper-alloy nickel-plated screw shell

### TESTING & CODE COMPLIANCE

- UL Listed (File #E-13402)
- CSA Certified (File #LR-1863)

