

# Standard Size Plastic and Metal Wallplates









## Standard Size

Single Receptacle, 15 and 20 AMP  
Straight Blade and 15 AMP Locking

### Residential Grade

### Commercial Grade

DESCRIPTION	COLOR	CAT. NO.	IND. NO.	METAL	CAT. NO.	IND. NO.
<b>1-GANG</b> 1-Single 1.406" dia. Hole 	IVORY	86004	P7-I	CHROME	*	—
	GRAY	87004	P7-GY	ALUM	83004	A7
	WHITE	88004	P7-W	BRASS	81004	B7
	BROWN	85004	P7	430 S/S	84004	S7
	ALMOND	82004	P7-A	302 S/S	84004-40	S7-N
<b>2-GANG</b> 2-Singles 1.406" dia. Holes 	IVORY	86052	P72-I	CHROME	*	—
	WHITE	88052	P72-W	ALUM	*	—
	BROWN	85052	P72	BRASS	*	—
				430 S/S	*	S72
<b>3-GANG</b> 3-Singles 1.406" dia. Holes 	—	—	—	302 S/S	84052-40	S72-N
				BRASS	*	—
<b>4-GANG</b> 4-Singles 1.406" dia. Holes 	—	—	—	430 S/S	*	S73
				302 S/S	S73-N	S73-N
<b>5-GANG</b> 5-Singles 1.406" dia. Holes 	—	—	—	BRASS	*	—
				430 S/S	*	S74
				302 S/S	*	S74-N
<b>6-GANG</b> 6-Singles 1.406" dia. Holes 	—	—	—	BRASS	*	—
				430 S/S	*	S75
				302 S/S	*	S75-N

\*Consult the end of this Wallplates section for ordering details; allow 3–4 weeks for delivery.  
All devices are UL Listed and CSA Certified.

