



Standard Size

Blank Plate — Strap Mount

DESCRIPTION		COLOR	Residential Grade		Commercial Grade		
DESCRIPTION		COLOR	CAT. NO.	IND. NO.	METAL	CAT. NO.	IND. NO.
6-GANG 6-Blanks, Strap Mount		—	—	—	BRASS	*	—
		—	—	—	430 S/S	*	—
7-GANG 7-Blanks, Strap Mount		—	—	—	302 S/S	*	S64-N
		—	—	—	BRASS	*	—
8-GANG 8-Blanks, Strap Mount		—	—	—	430 S/S	*	—
		—	—	—	302 S/S	*	S6014-N
8-GANG 8-Blanks, Strap Mount		—	—	—	BRASS	*	—
		—	—	—	430 S/S	*	—
8-GANG 8-Blanks, Strap Mount		—	—	—	302 S/S	*	S6024-N
		—	—	—	BRASS	*	—

Power Outlet Receptacle — One Gang — Mounting

DESCRIPTION		COLOR	CAT. NO.	IND. NO.	METAL	CAT. NO.	IND. NO.
1-GANG Power Outlet 2.15" dia. Hole Midway Use with 278, 279, 5206, 5207, 5371, 5372, 5373, 5374		IVORY	80528-I	P724-I	ALUM	83028	A724
		BLACK	80528-BLK	P724-BK	STEEL, BRASS FIN.	4928	B724
		WHITE	80528-W		STEEL, ALUM FIN.	4927	S724-GY
					430 S/S	84028	S724

Power Outlet Receptacle — Two Gang — Mounting

DESCRIPTION		COLOR	CAT. NO.	IND. NO.	METAL	CAT. NO.	IND. NO.
2-GANG Power Outlet 2.15" dia. Hole Midway Use with 278, 279, 5206, 5207, 5371, 5372, 5373, 5374		IVORY	80526-I	PJ703-I	BRASS	*	B703
		BLACK	80526-BLK	PJ703-BK	ALUM	83026	A703
		WHITE	80526-W	PJ703-W	STEEL, ALUM FIN.	4934	S703-GY
					430 S/S	84026	S703
2-GANG Power Outlet 2.465" dia. Hole		IVORY	80530-I		STEEL, ALUM FIN.	S701-GY	S701-GY
		BLACK	80530-BLK		430 S/S	*	S701
		WHITE	80530-W		302 S/S	S701-40	
		ALMOND	80530-A				
2-GANG Power Outlet 2.15" dia. Hole Offset		—	—	—	430 S/S	84022	S705
		—	—	—			

Locking Receptacle — One Gang

DESCRIPTION		COLOR	CAT. NO.	IND. NO.	METAL	CAT. NO.	IND. NO.
1-GANG 20A & 30A Locking 1.60" dia. Hole		—	—	—	BRASS	*	—
		—	—	—	430 S/S	*	—
1-GANG for Key Lock Power Switch 0.880" dia. Hole. Includes Tamper-Resistant Screws and Screwdriver		—	—	—	302 S/S	84020-40	S720-N
		—	—	—			
1-GANG for Key Lock Power Switch 0.880" dia. Hole. Includes Tamper-Resistant Screws and Screwdriver		—	—	—	302 S/S	84071-40	—
		—	—	—			

*Consult the end of this Wallplates section for ordering details: allow 3–4 weeks for delivery.
All devices are UL Listed and CSA Certified.