







## Standard Size




### Blank Plate — Strap Mount

Residential Grade				Commercial Grade		
DESCRIPTION	COLOR	CAT. NO.	IND. NO.	METAL	CAT. NO.	IND. NO.
 <b>6-GANG</b> 6-Blanks, Strap Mount	—	—	—	BRASS 430 S/S 302 S/S	* * *	— — S64-N
 <b>7-GANG</b> 7-Blanks, Strap Mount	—	—	—	BRASS 430 S/S 302 S/S	* * *	— — S6014-N
 <b>8-GANG</b> 8-Blanks, Strap Mount	—	—	—	BRASS 430 S/S 302 S/S	* * *	— — S6024-N



### Power Outlet Receptacle — One Gang — Mounting

DESCRIPTION	COLOR	CAT. NO.	IND. NO.	METAL	CAT. NO.	IND. NO.
 <b>1-GANG Power Outlet</b> 2.15" dia. Hole Midway Use with 278, 279, 5206, 5207, 5371, 5372, 5373, 5374	IVORY BLACK WHITE	80528-I 80528-BLK 80528-W	P724-I P724-BK	ALUM STEEL, BRASS FIN. STEEL, ALUM FIN. 430 S/S	83028 4928 4927 84028	A724 B724 S724-GY S724

### Power Outlet Receptacle — Two Gang — Mounting

DESCRIPTION	COLOR	CAT. NO.	IND. NO.	METAL	CAT. NO.	IND. NO.
 <b>2-GANG Power Outlet</b> 2.15" dia. Hole Midway Use with 278, 279, 5206, 5207, 5371, 5372, 5373, 5374	IVORY BLACK WHITE	80526-I 80526-BLK 80526-W	PJ703-I PJ703-BK PJ703-W	BRASS ALUM STEEL, ALUM FIN. 430 S/S	* 83026 4934 84026	B703 A703 S703-GY S703
 <b>2-GANG Power Outlet</b> 2.465" dia. Hole	IVORY BLACK WHITE ALMOND	80530-I 80530-BLK 80530-W 80530-A		STEEL, ALUM FIN. 430 S/S 302 S/S	S701-GY * S701-40	S701-GY S701
 <b>2-GANG Power Outlet</b> 2.15" dia. Hole Offset	—	—	—	430 S/S	84022	S705

### Locking Receptacle — One Gang

DESCRIPTION	COLOR	CAT. NO.	IND. NO.	METAL	CAT. NO.	IND. NO.
 <b>1-GANG 20A &amp; 30A Locking</b> 1.60" dia. Hole	—	—	—	BRASS 430 S/S 302 S/S	* * 84020-40	— — S720-N
 <b>1-GANG for Key Lock Power</b> Switch 0.880" dia. Hole. Includes Tamper-Resistant Screws and Screwdriver	—	—	—	302 S/S	84071-40	—

\*Consult the end of this Wallplates section for ordering details: allow 3–4 weeks for delivery.  
 All devices are UL Listed and CSA Certified.