



Portable Test Equipment

TS22®A
Test Set with
Speakerphone

hands free

two-way

speakerphone

The TS22A test set combines all the productivity, safety and reliability features of the TS22 test set plus a speakerphone for true hands free communication out in the field. All this adds up to improved functionality, less on-the-job stress and greater convenience.



Features:

- Speakerphone for hands free two-way conversations
- Tone (DTMF) and pulse operation
- Last number redial
- DTMF signal levels compensated for loop length
- DropSafe™ unit up to 20 feet
- Audible electronic ringer
- Locking mute switch
- 3-year redial storage time
- High impedance monitor for DataSafe™ operation
- Over voltage and over current protection
- PBX pause button
- Field replaceable belt clip
- Continuous polarity LED indications
- For use with computerized voice response systems
- Stores nine 18-digit numbers in repertory dialer (speed dialing)
- RainSafe™ test set for use in extreme weather conditions

Part Numbers:

- TS22A with Standard Angled Piercing Pin ClipsP/N 22801-001
- TS22A with 346A Plug CordP/N 22801-004
- TS22A with Ground Start CordP/N 22801-007
- TS22A with 346A Plug and 1500 Ohm Resistor/Switch Cord.....P/N 22801-008
- TS22A with Angled Bed-of-Nails CordP/N 22801-009



Network Support Division
809 Calle Plano, Camarillo, CA
93012-8519 USA
www.harris.com

1-800-437-2266 or 1-805-987-9511

PB No. 3013a 4/99

TS22 is a registered trademark of Harris Corporation. DataSafe, RainSafe and DropSafe are trademarks of Harris Corporation. All other trademarks belong to their respective companies.

© 1999 HARRIS CORPORATION

next level solutions

