

Sold by:



Haven's™ Grips

Klein Haven's™ Grips

- Designed for use when light, compact grip is desired and where conductor damage is not a factor.
- Gripping pressure of the knurled jaw is applied to 1/4" (6.35 mm) cable area.
- Cat Nos. 1604-20L and 1625 series have a swing latch to help hold cable in the jaw.



1604-20

AWG/B&S Wire Gauges

Diameters of American (AWG) or Brown & Sharpe (B&S) Wire Gauges			
No. of Wire Gauge	American (AWG) or Brown & Sharpe (B&S)	No. of Wire Gauge	American (AWG) or Brown & Sharpe (B&S)
0000	.460"	19	.03589"
000	.40964"	20	.031961"
00	.3648"	21	.028462"
0	.32486"	22	.025347"
1	.2893"	23	.022571"
2	.25763"	24	.0201"
3	.22942"	25	.0179"
4	.20431"	26	.01594"
5	.18194"	27	.014195"
6	.16202"	28	.012641"
7	.14428"	29	.011257"
8	.12849"	30	.010025"
9	.11443"	31	.008928"
10	.10189"	32	.00795"
11	.090742"	33	.00708"
12	.080808"	34	.006304"
13	.071961"	35	.005614"
14	.064084"	36	.005"
15	.057068"	37	.004453"
16	.05082"	38	.003965"
17	.045257"	39	.003531"
18	.04030"	40	.003144"

Cat. No.	Minimum Cable	Maximum Cable	Maximum Safe Load	Approx. Weight Each
1604-10	14 B&S .06" (1.52 mm)	2 B&S .25" (6.35 mm)	2500 lbs. (1136 kg)	1 lb. (.45 kg)
1604-20	8 B&S solid .125" (3.18 mm)	steel strand .50" (12.70 mm)	5000 lbs. (2272 kg)	2-1/12 lbs. (1.14 kg)



1604-20L

Cat. No.	Minimum Cable	Maximum Cable	Maximum Safe Load	Approx. Weight Each
1604-20L	8 B&S solid .125" (3.18 mm)	steel strand .50" (12.70 mm)	5000 lbs. (2272 kg)	2-1/12 lbs. (1.14 kg)



1625-20

Cat. No.	Minimum Cable	Maximum Cable	Maximum Safe Load	Approx. Weight Each
1625-20	1 B&S .28" (7.11 mm)	wire rope .75" (19.05 mm)	8000 lbs. (3636 kg)	4 lbs. (1.81 kg)
1625-20 7/8	.38" (9.65 mm)	wire rope .88" (22.35 mm)	8000 lbs. (3636 kg)	4 lbs. (1.81 kg)
1625-20 1	.50" (12.70 mm)	wire rope 1" (25.40 mm)	8000 lbs. (3636 kg)	4 lbs. (1.81 kg)

All dimensions are in inches and (millimeters) unless otherwise specified.

▲WARNING: Grips are to be used for temporary installation, not for permanent anchorage.

▲WARNING: When used on/or near energized lines, ground, insulate, or isolate grip before pulling.

▲WARNING: Do not exceed rated capacity.

▲WARNING: Before each use, clean jaw area and inspect grip for proper operation to avoid slippage.

▲WARNING: Always match proper size and type of grip to application.

Wire Pulling Grips

