

Straight Blade Plugs and Connectors



Industrial Grade

20 AMP Power Plugs

20 AMP 125/250V Straight Blade Plugs 3-Pole 3-Wire Non-Grounding

DESCRIPTION	CAT. NO.	MATCHING RECEPTACLE	NEMA CONFIG.
Straight Plug	9151-N	5032 5032-I	10-20P

20 AMP 120/208V 4-Pole, 4-Wire, 3ØY Non-Grounding

Straight Plug★	7251-C	7250-FR	18-20P
----------------	--------	---------	--------

30 AMP Nylon Angle Plugs

30 AMP 125V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	MATCHING RECEPTACLE	NEMA CONFIG.
Angle Plug	9530-P	5371 5371-IG	5-30P

30 AMP 250V 2-Pole 3-Wire Grounding

Angle Plug	9630-P	5372 5372-IG	6-30P
------------	--------	-----------------	-------

30 AMP 277V 2-Pole 3-Wire Grounding

Angle Plug	9730-P	9730-A	7-30P
------------	--------	--------	-------

30 AMP 125/250V 3-Pole 3-Wire Non-Grounding

Angle Plug	9332-P	5207	10-30P
------------	--------	------	--------

30 AMP 125/250V 3-Pole 4-Wire Grounding

Angle Plug	9432-P	278	14-30P
------------	--------	-----	--------

30 AMP 250V 3-Pole 4-Wire 3-Phase Grounding

Angle Plug	8432-P	8430	15-30P
------------	--------	------	--------

30 AMP 120/208V 4-Pole 4-Wire 3ØY Non-Grounding

Angle Plug	8332-P	8330	18-30P
------------	--------	------	--------

All devices are UL Listed. Also CSA Certified except where indicated by★



9432-P



9530-P

SPECIFICATIONS & FEATURES

- Rugged cord clamps for secure cable grip that accommodate cord diameters from 5/8" to 1-3/8" and do not tear conductor jacket
- Made of tough, heavy-duty nylon for long service life
- Devices feature heavy-sectioned dead-front right-angle
- Pressure-clamp terminal design
- Terminals accept up to #4AWG stranded conductors
- Four-way positioning front module
- Solid brass blades for maximum conductivity

TESTING & CODE COMPLIANCE

- UL Listed (File #13393)
- UL Test 498 (CSA 42)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2
Operating Temperature: -40°C to 65°C



For more information regarding matching receptacles, refer to Receptacles, Section D.

