

Description:

Series NS Horn Strobes & Series NH Horn Appliances are ideal for wall mount designs that require 2 wire installation and 2 selectable dBA settings (90 & 95).

Strobe Options:

Single Candela **Wall:** 1575 cd
Multi Candela Field Selectable **Wall:** 15/30/75/110 cd

Features:

- Selectable Continuous Horn or Temporal (Code 3)
- 2 Selectable dBA settings of 90 and 95 dBA in both tones
- Patented Universal Mounting Plate
- Wall mount
- Synchronize strobe and audible with Wheelock SM, DSM Sync Modules or PS-12/24-8MP Power Supply with built-in sync protocol



Series NS



Series NH

Specification and Ordering Information

Model Number	Order Code	Strobe Candela	24 VDC	12 VDC	2 WIRE	Model Color Red	Model Color White	Mounting Options#	Agency Approvals				
									UL	MEA	CSFM	FM	BFP
NS-24MCW-FR	9404	15/30/75/110	X	-	X	X	-	B,D,E,F,G,H,J,N,O,P,R,X	X	X	X	X	X
NS-24MCW-FW	9405	15/30/75/110	X	-	X	-	X	B,D,E,F,G,H,J,N,O,P,R,X	X	X	X	X	X
NS-241575W-FR	7806	15 (75 on Axis)	X	-	X	X	-	B,D,E,F,G,H,J,N,O,P,R,X	X	X	X	X	X
NS-241575W-FW	7811	15 (75 on Axis)	X	-	X	-	X	B,D,E,F,G,H,J,N,O,P,R,X	X	X	X	X	X
NS-121575W-FR	7816	15 (75 on Axis)	-	X	X	X	-	B,D,E,F,G,H,J,N,O,P,R,X	X	X	X	X	X
NS-121575W-FW	7818	15 (75 on Axis)	-	X	X	-	X	B,D,E,F,G,H,J,N,O,P,R,X	X	X	X	X	X
NH-12/24-R	7449	-	X	X	X	X	-	B,D,E,F,G,H,J,N,O,P,R,X	X	X	X	X	X
NH-12/24-W	7500	-	X	X	X	-	X	B,D,E,F,G,H,J,N,O,P,R,X	X	X	X	X	X

#See mounting options pull out guide in the last section of this binder.
X = Approved
* = Pending

Average RMS Current

Series NS/NH 24 VDC		Audible	Wall Mount Audible Strobe Models				
		NH-12/24	NS-241575W	NS-24MCW			
		@24VDC	1575cd	15cd	30cd	75cd	110cd
High (95) dBA	24 VDC	0.028	0.094	0.065	0.087	0.134	0.174
Low (90) dBA	24 VDC	0.022	0.093	0.052	0.072	0.126	0.158
Series NS/NH 12 VDC		Audible	Wall Mount Aud/Strobe				
		NH-12/24	NS-121575W				
		@12V	1575cd				
High (89) dBA	12 VDC	0.019	0.251				
Low (84) dBA	12 VDC	0.015	0.265				

