

Description:

Wheelock's bells offer low power consumption with high sound. Various models are available to accommodate different applications and voltage requirements.

Features:

- Approvals: UL Standard 464 Listed, Factory Mutual (FM), California State Fire Marshal (CSFM), New York (MEA) and Chicago (BFP)
- Weatherproof design (WBB backbox required - Order Code 2411)
- Aluminum bell housing
- Integral RFI suppression
- Screw terminal connections



Series 43T



Series 43T AC Vibrating Bells

- Solenoid driven
- Applications: Alarms, Doorbells, Gates

Series MB DC Vibrating Motor Bells

- Motor Driven
- Applications: Alarms, Doorbells, Gates

Specification and Ordering Information

Model Number	Order Code	Applications	Shell Size	Input Voltage	Input Current	dBA @ 10 Feet	Mounting Options#	Agency Approvals				
								UL	MEA	CSFM	FM	BFP
AC Vibrating Bells (Solenoid Driven)												
43T-G6-24-S	1626	Alarms Doorbells Gates	6"	24 VAC	.410	86	D,E,J,K,R,S,Z	X	X	X	X	X
43T-G6-115-S	1630		6"	115 VAC	.085	86		X	X	X	X	X
43T-G10-24-S	3800		10"	24 VAC	.410	88		X	X	X	X	X
43T-G10-115-S	3693		10"	115 VAC	.085	88		X	X	X	X	X
DC Vibrating Bells												
MB-G6-12-S	4221	Alarms Doorbells Gates	6"	12 VDC	.060	92	D,E,J,K,R,S,Z	X	X	X	X	X
MB-G6-24-S	4222		6"	24 VDC	.030	92		X	X	X	X	X
MB-G10-12-S	4223		10"	12 VDC	.060	92		X	X	X	X	X
MB-G10-24-S	4224		10"	24 VDC	.030	92		X	X	X	X	X
MB-G6-6-R	4884	Elevators	6"	6 VDC	.090	90		X	X	X	X	X

#See mounting options pull out guide in the last section of this binder.

X = Approved

* = Pending

