

Series SA Self Amplified Paging Horns



SA-H5B, SA-H15B

Specification and Ordering Information

Model Number	Order Code	Description	Power Output @ 1000 Hz/Nominal Current	dBA @ 1 Meter	Frequency Response	Mounting
SA-H5B	5145	8" Dia. X D Weatherproof Re-entrant Horn, Metal, Beige	5 Watts/325 mA	118	275 Hz - 10 KHz	Universal, Fully Adjustable Mounting Base w/ Banding Slots for Beams or Pillars. Conduit Interface Adapter w/ Clear Plastic Shield
SA-H15B	5146	8" Dia. X D Weatherproof Re-entrant Horn, Metal, Beige	15 Watts/1.4 Amps 7.5 Watts/900mA	122	275 Hz - 10 KHz	Universal, Fully Adjustable Mounting Base w/ Banding Slots for Beams or Pillars. Conduit Interface Adapter w/ Clear Plastic Shield

SA Series speakers have barriered, clamp type screw terminals, impedance: 600 Ohms/operating voltage: 18-28 VDC
Sound output (dBA @ 1 meter) measured at rated power output at 100 Hz.

Series VC Wall Mount Volume Controls

Description:

Wheelock's VC-10 and VC-35 attenuators are ideal for controlling the volume of a single speaker or a group of speakers on a 25V or 70V line.

Features:

- Auto-transformer design for best efficiency
- Stainless steel wall plate
- Rotary switch that attenuates in 3dB steps to a completely off position

Specification and Ordering Information

Model Number	Order Code	Power Handling	Frequency Response	Insertion Loss	Wall Plate
VC-10	5159	10 Watts	Better than 17 KHz	Less than .5dB	Single Gang
VC-35	5160	35 Watts	Better than 17 KHz	Less than .5dB	Double Gang



VC-35

