

Canada Tel: 800-435-0786 Intern Fax: 800-524-2853

## Ultra Tugger™ Speed Booster



CAT. NO.	UPC NO.	DESCRIPTION	
03561	03561	Ultra Tugger™ Speed Booster	
04884	04884	Ultra Tugger <sup>™</sup> Cord and Plug kit	



- The Ultra Tugger<sup>™</sup> Speed Booster increases the speed of the Ultra Tugger<sup>™</sup> to pull approximately twice as fast as normal, up to 2,500 lbs. (11.1 kN).
- For use with the Greenlee Ultra Tugger<sup>™</sup> cable puller only.
- Increases productivity on lower force runs and during the initial phase of a high force pull.
- Automatically switches to low speed at 2,500 lbs (11.1 kN) to protect the puller motor.
- Ultra Tugger<sup>™</sup> adapter cord and plug included.

SPECIFICATIONS			
Capacity	0 to 2,500 lbs. (11.1 kN) pulling force in high speed mode.		
Dimensions	Height: 9.5" (241.3 mm); Width: 13" (330.2 mm); Depth: 15.5" (393.7 mm)		
Weight	46 lbs. (20.9 kg)		
Pulling Speed	No Load – 18 fpm (5.5 m); At 2000 lbs. (8.8 kN) – 16 fpm (4.9 m)		
Power	115 VAC, 15A Input; 115/230 VAC, 15/6A Output		

## Ultra Tugger™ Slip-in Couplings



Size 2-1/2"- 5" EMT, IMC or Rigid				
Weight 00804 - 6 lbs. (2.7 kg) 00820 - 11 lbs. (5 kg)   00811 - 7 lbs. (3.2 kg) 00827 - 13 lbs. (5.8 grad)   00815 - 9 lbs. (4.1 kg) 00827 - 13 lbs. (5.8 grad)	·/			

- Use to attach the Versi-Boom<sup>™</sup> to the conduit.
- Couplings slip into the conduit and pin to the Versi-Boom<sup>™</sup>.
- For use with the Versi-Boom<sup>™</sup> System only.

CAT. NO.	UPC NO.	SIZE	WEIGHT	
00804	00804	2.5"	6 lbs (2.7 kg)	
00811	00811	3"	7 lbs (3.2 kg)	
00815	00815	3.5"	9 lbs (4.1 kg)	
00820	00820	4"	11 lbs (5 kg)	
00827	00827	5"	13 lbs (5.8 kg)	

## Ultra Tugger™ Screw-on Couplings



## SPECIFICATIONS

Size	2-1/2"-	4" EMT.	IMC or	Riaid

Weight	00868 - 22 lbs. (10.0 kg)	00781 - 3 lbs. (1.36 kg)
mongine	00000 LL 100. (10.0 kg/	00101 0 100. (1.00 hg)

- Use to attach the Versi-Boom<sup>™</sup> to the conduit when pulling from overhead.
- The coupling and adapter threads onto the conduit and pins to the Versi-Boom<sup>™</sup>.
- The Screw-on coupling and adapter must be used together. One adapter fits all of the screw-on couplings.

CAT.	NO. UPC NO	. DESCRIPTION
0086	68 00868	Screw-on Coupler Set for 2-1/2", 3", 3-1/2", and 4" conduit.
0366	03661	Optional Screw-on Coupling for 2" conduit.
0078	00781	Optional Screw-on Coupling for 2-1/2" conduit.