

Sold by:



International-Rated Pin & Sleeve Devices



Engineered to IP44
Splashproof Standards
International Rated Devices



Engineered to UL & IEC
Watertight Standards
432P3WL, 432C3WL & All 125A Devices Listed On
This Page Have North American Rated Construction

**2 YEAR LIMITED
WARRANTY**



International-Rated Devices

Leviton offers international-rated pin and sleeve devices available in 16, 32, 63 and 125 Amps. These IEC 309-1 and 309-2 compliant devices are ideal for use overseas where voltage and amperage requirements differ from North American standards, but where rigorous performance, quality, and reliability criteria need to be met.

16, 32 and 63 Amp devices have an environmental classification of splashproof (IP44), and 125 Amp devices are classified as watertight (IP67).

Ordering Information*

| AMPS | WIRING | VOLTAGE AC | CONNECTOR/RECEPTACLE | PLUG/INLET | PLUG | CONNECTOR | RECEPTACLE | INLET |
|------|--------|-------------------|----------------------|------------|----------|-----------|------------|---------|
| 16 | 2p3w | 100 - 130 | | | SP316P4 | SP316C4 | SP316R4 | SP316B4 |
| | 2p3w | 250 | | | SP316P6 | SP316C6 | SP316R6 | SP316B6 |
| | 3p4w | 380 - 415 | | | SP416P6 | SP416C6 | SP416R6 | SP416B6 |
| | 4p5w | 200/346 - 240/415 | | | SP516P6 | SP516C6 | SP516R6 | SP516B6 |
| 32 | 2p3w | 100 - 130 | | | SP332P4 | SP332C4 | SP332R4 | SP332B4 |
| | 2p3w | 250 | | | SP332P6 | SP332C6 | SP332R6 | SP332B6 |
| | 3p4w | 380 - 415 | | | SP432P6 | SP432C6 | SP432R6 | SP432B6 |
| | 3p4w | 3Ø380 - 3Ø440 | | | 432P3WL† | 432C3WL† | — | — |
| | 4p5w | 200/346 - 240/415 | | | SP532P6 | SP532C6 | SP532R6 | SP532B6 |
| 63 | 2p3w | 250 | | | SP363P6 | SP363C6 | SP363R6 | SP363B6 |
| | 3p4w | 380 - 415 | | | SP463P6 | SP463C6 | SP463R6 | SP463B6 |
| | 4p5w | 200/346 - 240/415 | | | SP563P6 | SP563C6 | SP563R6 | SP563B6 |
| 125 | 2p3w | 250 | | | 3125P6W | 3125C6W | 3125R6W | 3125B6W |
| | 3p4w | 380 - 415 | | | 4125P6W | 4125C6W | 4125R6W | 4125B6W |
| | 4p5w | 200/346 - 240/415 | | | 5125P6W | 5125C6W | 5125R6W | 5125B6W |

*Consult the factory for availability before placing your order. These are specialty order items and are not regularly stocked.

† This device has North American 30 Amp construction and is used in refrigerated container applications.