



International-Rated Pin & Sleeve Devices



Engineered to IP44
Splashproof Standards
International Rated Devices



Engineered to UL & IEC
Watertight Standards
432P3WL, 432C3WL & All 125A Devices Listed On
This Page Have North American Rated Construction

**2 YEAR LIMITED
WARRANTY**



SP516P6

SP516C6

SP516R6

SP516B6

International-Rated Devices

Leviton offers international-rated pin and sleeve devices available in 16, 32, 63 and 125 Amps. These IEC 309-1 and 309-2 compliant devices are ideal for use overseas where voltage and amperage requirements differ from North American standards, but where rigorous performance, quality, and reliability criteria need to be met.

16, 32 and 63 Amp devices have an environmental classification of splashproof (IP44), and 125 Amp devices are classified as watertight (IP67).

Ordering Information*

AMPS	WIRING	VOLTAGE AC	CONNECTOR/RECEPTACLE	PLUG/INLET	PLUG	CONNECTOR	RECEPTACLE	INLET
16	2p3w	100 - 130			SP316P4	SP316C4	SP316R4	SP316B4
	2p3w	250			SP316P6	SP316C6	SP316R6	SP316B6
	3p4w	380 - 415			SP416P6	SP416C6	SP416R6	SP416B6
	4p5w	200/346 - 240/415			SP516P6	SP516C6	SP516R6	SP516B6
32	2p3w	100 - 130			SP332P4	SP332C4	SP332R4	SP332B4
	2p3w	250			SP332P6	SP332C6	SP332R6	SP332B6
	3p4w	380 - 415			SP432P6	SP432C6	SP432R6	SP432B6
	3p4w	3Ø380 - 3Ø440			432P3WL†	432C3WL†	—	—
	4p5w	200/346 - 240/415			SP532P6	SP532C6	SP532R6	SP532B6
63	2p3w	250			SP363P6	SP363C6	SP363R6	SP363B6
	3p4w	380 - 415			SP463P6	SP463C6	SP463R6	SP463B6
	4p5w	200/346 - 240/415			SP563P6	SP563C6	SP563R6	SP563B6
125	2p3w	250			3125P6W	3125C6W	3125R6W	3125B6W
	3p4w	380 - 415			4125P6W	4125C6W	4125R6W	4125B6W
	4p5w	200/346 - 240/415			5125P6W	5125C6W	5125R6W	5125B6W

*Consult the factory for availability before placing your order. These are specialty order items and are not regularly stocked.

† This device has North American 30 Amp construction and is used in refrigerated container applications.