



### 15 AMP Non-NEMA Locking Devices

15 AMP 125V/10A-250 3-Pole 3-Wire Non-Grounding Non-NEMA†

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NON-NEMA CONFIG.
Single Flush Receptacle★	7582**			
Locking Plug★	7567-C*	.245-.700	10-18	NON-NEMA
Locking Connector★	7565-C*	.245-.700	10-18	
Locking Flanged Inlet★	7556			NON-NEMA
Locking Flanged Outlet★	7557			

†These devices are no longer UL Listed and are for replacement use only. Add (-G) for grounding version.  
\*Grounding (-G) version not available. For grounding connector, use Cat. No. 7555-G  
\*\*Uses stainless steel wallplate, Cat. No. 84004-40.



### 20 AMP Non-NEMA Locking Devices

20 AMP 250V AC/DC / 10 AMP 600V AC 4-Pole 5-Wire Grounding Non-NEMA

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NON-NEMA CONFIG.
Single Flush Receptacle★	3520Δ			
Locking Plug, Black Nylon Body★	3521-C	.595-.895	10-18	NON-NEMA
Locking Connector, Black Nylon Body★	3523-C	.595-.895	10-18	
Locking Flanged Inlet★	3524-C			NON-NEMA
Locking Flanged Outlet★	3525-C			

20 AMP, 125V/250V 3-Pole 3-Wire Non-Grounding Non-NEMA††

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NON-NEMA CONFIG.
Single Flush Receptacle★	7310-BΔ			
Locking Plug★	9965-C	.385-.780	10-18	NON-NEMA
Locking Connector★	7314-C	.385-.780	10-18	
Locking Flanged Inlet★	3325-C			NON-NEMA
Locking Flanged Outlet★	3326-C			

20 AMP 3ØY 120V/208V 4-Pole 4-Wire Non-Grounding Non-NEMA††

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NON-NEMA CONFIG.
Single Flush Receptacle★	7410-BΔ			
Locking Plug★	7411-C	.595-.895	10-18	NON-NEMA
Locking Connector★	7413-C	.595-.895	10-18	
Locking Flanged Inlet★	7408-C			NON-NEMA
Locking Flanged Outlet★	7409-C			

††Effective July 1, 1981, rating for non-grounding versions was changed from 20A-250V AC/DC, 10A-600V AC to comply with UL requirements. Add (-G) for grounding devices: (-G) devices are rated 20A-250V AC/DC, 10A-600V AC and are no longer UL Listed — for replacement use only.

For Corrosion Resistant Locking Devices, please check pages K2-K5  
ΔUses stainless steel wallplate, Cat. No. 84020-40. For additional wallplate selections, please see Section G.  
Weather-Resistant Boots for 15A & 20A Locking Plugs and Connectors are listed on page J20  
All devices are UL Listed. Also CSA certified except where indicated by★

#### SPECIFICATIONS & FEATURES

- Locking Receptacles feature a complete range of ratings and Non-NEMA configurations, non-grounding
- Locking Plugs and Connectors feature heavy-duty construction for top performance in the environmental extremes of grueling industrial settings
- Flanged Inlets and Outlets are built to endure hard use with rugged nylon flanges that assure a smooth, flush fit and outstanding resistance to cracking and breaking

#### TESTING & CODE COMPLIANCE

- All receptacles, plugs, connectors, inlets and outlets are designed to meet NEMA WD-6, and ANSI C-73, and to meet/exceed UL 498 standards
- UL Fed Spec. Listed WC-596 (File #E-13399 — Cat. Nos. 7582, 7557, 3520, 2525-C, 7310-B, 3326-C, 7410-B, 7409-C; File #E-13393 — Cat. Nos. 7567-C, 7565-C, 7556, 3521-C, 3523-C, 3524-C, 9965-C, 7314-C, 3325-C, 7411-C, 7413-C, 7408-C)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Lifetime Warranty

#### MATERIAL CHARACTERISTICS

Environmental: Flammability per UL94 or CSA C22/06 Requirements  
Operating Temperature: -40°C to 60°C

