





15 AMP Locking Devices

15 AMP 250V 2-Pole 3-Wire Grounding

| DESCRIPTION | CAT. NO. | CORD DIA. (inches) | WIRE GAUGE (stranded) | NEMA CONFIG. |
|---|-----------|--------------------|-----------------------|--|
| Duplex Flush Receptacle, Self Grounding, Back and Side Wired | 4550 | | | |
| Duplex Flush Receptacle, Isolated Ground, Back and Side Wired | 4550-IG | | | |
| Single Flush Receptacle | 4560** | | | |
| Single Flush Receptacle, w/Short Strap | 4560-SS | | | |
| Single Flush Receptacle, Isolated Ground | 4560-IG** | | | L6-15R  |
| Single Flush Receptacle, Isolated Ground, w/Short Strap | 4560-SIG | | | |
| Locking Plug, Black Nylon Body | 4570-C | .245-.700 | 10-18 | L6-15P  |
| Angle Locking Plug, Black Nylon Body | 4570-CA | .245-.700 | 10-18 | |
| Locking Plug, Yellow Nylon Body | 4570-CY | .245-.700 | 10-18 | |
| Locking Connector, Black Nylon Body | 4579-C | .245-.700 | 10-18 | |
| Locking Connector, Yellow Nylon Body | 4579-CY | .245-.700 | 10-18 | |
| Locking Flanged Outlet | 4585-C | | | |
| Locking Flanged Inlet | 4586-C | | | |

15 AMP 277V 2-Pole 3-Wire Grounding

| DESCRIPTION | CAT. NO. | CORD DIA. (inches) | WIRE GAUGE (stranded) | NEMA CONFIG. |
|---|-----------|--------------------|-----------------------|--|
| Duplex Flush Receptacle, Self Grounding, Back and Side Wired | 4750 | | | |
| Duplex Flush Receptacle, Isolated Ground, Back and Side Wired | 4570-IG | | | |
| Single Flush Receptacle | 4760** | | | |
| Single Flush Receptacle, w/Short Strap | 4760-SS | | | |
| Single Flush Receptacle, Isolated Ground | 4760-IG** | | | |
| Single Flush Receptacle, Isolated Ground, w/Short Strap | 4760-SIG | | | L7-15R  |
| Locking Plug, Black Nylon Body | 4770-C | .245-.700 | 10-18 | |
| Lighted Locking Plug, Black Nylon Body | 4770-PLC | .245-.700 | 10-18 | L7-15P  |
| Angle Locking Plug, Black Nylon Body | 4770-CA | .245-.700 | 10-18 | |
| Locking Plug, Yellow Nylon Body | 4770-CY | .245-.700 | 10-18 | |
| Locking Connector, Black Nylon Body | 4779-C | .245-.700 | 10-18 | |
| Locking Connector, Yellow Nylon Body | 4779-CY | .245-.700 | 10-18 | |
| Lighted Locking Connector, Black Nylon Body | 4779-PLC | .245-.700 | 10-18 | |
| Locking Flanged Outlet | 4785-C | | | |
| Locking Flanged Inlet | 4786-C | | | |

**Uses stainless steel wallplate, Cat. No. 84004-40. For additional wallplate selections, please see Section G.
 For Corrosion Resistant Locking Devices, please check pages K2-K5
 Weather-Resistant Boots for 15A Locking Plugs and Connectors are listed on page J20
 All devices are UL Listed and CSA certified.



SPECIFICATIONS & FEATURES

- Locking Receptacles feature a complete range of ratings and NEMA configurations, including isolated ground and non-grounding
- Locking Plugs and Connectors feature heavy-duty construction for top performance in the environmental extremes of grueling industrial settings
- Flanged Inlets and Outlets are built to endure hard use with rugged nylon flanges that assure a smooth, flush fit and outstanding resistance to cracking and breaking

TESTING & CODE COMPLIANCE

- All receptacles, plugs, connectors, inlets and outlets are designed to meet NEMA WD-6, and ANSI C-73, and to meet/exceed UL 498 standards
- UL Fed Spec. Listed WC-596 (File #E-13399 — Cat. Nos. 4550, 4560, 4585-C, 4750, 4760, 4785-C; File #E-13393 — Cat. Nos. 4570, 4579, 4586-C, 4770, 4779, 4786-C)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Lifetime Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability per UL94 or CSA C22/06 Requirements
 Operating Temperature: -40°C to 60°C

