



Country United States

[Home](#) [Sign In](#) [My Lists](#) [Knowledgebase](#) [Customer Support](#) [Buy Now!](#)[Search](#)[About](#) [Products](#) [Solutions](#) [Library](#) [ez-Tools](#) [Affiliates](#) [Distribution](#) [OEM](#) [Retail](#) [International](#) [What's New](#)[Wiring Devices](#)[Network Solutions](#)[Lighting Controls](#)[Entertainment](#)[Home Automation](#)[Connected Home](#)[Energy Management](#)[Electric Car Charging](#)[Data Center](#)[Sub-Metering](#)[Leviton.com](#) > [All Products](#) > [Locking Devices](#) > [Connectors](#) > 29W76 [ZOOM](#)Quantity: [Add to Project List](#)[Product Spec / Info](#)[Print / Email](#)

Color: Yellow



NEMA: L16-30R



## 29W76

UPC Code: 07847796879

Country of Origin: United States - *\*Eligible for ARRA funded projects*

### Description

30 Amp, 480 Volt 3-Phase, NEMA L16-30R, 3P, 4W, Locking Connector, Industrial Grade, Grounding, Wetguard - Yellow

### Additional Product Information

- [Dimensional Drawing](#)
- [Product Brochure](#)
- [Wiring Diagram](#)

### Product Features

NEMA: L16-30R

Color: Yellow

ez-find<sup>®</sup>[\\*Disclaimer](#)

#### Electrical Specifications

Grounding:	Grounding
Amperage:	30 Amp
Voltage:	480 Volt 3-Phase
Pole:	3
Wire:	4
Dielectric Voltage:	Withstands 2000V per UL498
Current Limiting:	Full Rated Current
Temperature Rise:	Max 30C after 250 cycles OL at 200 percent rated current

#### Environmental Specifications

Flammability:	Rated V-2 per UL94
Operating Temperature:	-40C to 60C

#### Material Specifications

Body Material:	Santoprene TPV
Compression Nut, Strain Relief:	Nylon
Body Interior:	Nylon
Wire Module:	Nylon
Bushing:	Santoprene TPV
Blades/Contacts:	Electroless Nickel-coated Brass
Terminal Screws:	Electroless Nickel-coated Brass
Assembly Screws:	Stainless Steel, Non-Magnetic

#### Mechanical Specifications

Terminal ID:	Brass-Hot, Green-Ground, Silver-Neutral
Terminal Accom:	#12 to #8
Product ID:	Ratings and NEMA I.D. permanently marked on device
Cord Grip Range (in):	.625-1.125

#### Standards and Certifications

NEMA:	WD-6
ANSI:	C-73
UL:	498
CSA C22.2 No. 42:	File LR-406
NOM:	057
Warranty:	Lifetime Warranty

