



50 AMP Devices

50 AMP 125V 2-Pole 3-Wire Grounding Non-NEMA

DESCRIPTION	CAT. NO.	NON-NEMA CONFIG.
Locking Plug, Yellow Nylon Body and Cord Clamp	6361-CR	 RECEPTACLE
Locking Connector, Yellow Nylon Body and Cord Clamp	6360-CR	
Single Locking Flush Receptacle	6370-CR	
Power Inlet, 316 Stainless Steel w/Threaded Cap	6372-CR	

50 AMP 125/250V 3-Pole 4-Wire Grounding Non-NEMA

DESCRIPTION	CAT. NO.	NON-NEMA CONFIG.
Locking Plug, Yellow Nylon Body and Cord Clamp	6365-CR	 RECEPTACLE
Locking Connector, Yellow Nylon Body and Cord Clamp	6364-CR	
Single Locking Flush Receptacle	6369-CR	
Power Inlet, 316 Stainless Steel w/Threaded Cap	6374-CR	

Boots and Covers for 50 AMP Corrosion Resistant Devices

DESCRIPTION	CAT. NO.
50A Locking Plug Boot, High Visibility Yellow	7717-CR
50A Locking Connector Boot, High Visibility Yellow	7715-CR
Sealing Collar for 7715-CR & 7717-CR	510-R
Weatherproof Receptacle Cover with Lift Lid, Yellow Lexan	7788-CR

All devices are UL Listed only, not CSA Certified.



SPECIFICATIONS & FEATURES

- All current-carrying metal parts (blades, contacts, terminals and screws) are electroless nickel-coated
- Color coded wire entrance holes for simple and easy wiring
- Beveled rear housing prevents cord from getting caught on stairs, equipment, etc.
- Nylon plug and connector body are bright yellow for easy corrosion resistant identification
- Ribbed nylon housing for excellent impact resistance and secure gripping
- Neoprene gasket helps keep dirt and dust from entering termination area
- Stainless steel cord clamp opens wide for direct terminal access; added strip length for easy wire insertion into terminals
- Interior cord clamp opens wide to allow easy insertion of wires into terminals
- Longer contacts inside connector assure stronger, tighter fitting contact points

TESTING & CODE COMPLIANCE

Receptacles

- UL Listed (File #E-111198)

Plugs & Connectors

- UL Listed (File #E-57672)
- Telephone connecting devices are in accordance with Federal Communications Standards

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated UL94 V0

Operating Temperature: 125°C continuous (plugs & connectors)

130°C continuous (receptacles)

Sold by:

