





Sold by:





20 AMP Locking Devices

20 AMP 3ØY 347/600V 4-Pole 5-Wire Grounding



DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NEMA CONFIG.
Single Flush Receptacle	2530†			
Single Flush Receptacle, Isolated Ground	2530-IG†			L23-20R 
Locking Plug, Black Nylon Body	2531	.595-.895	10-18	
Locking Connector, Black Nylon Body	2533	.595-.895	10-18	L23-20P 
Locking Flanged Inlet	2545			
Locking Flanged Outlet	2546			

30 AMP Locking Devices

30 AMP 125V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NEMA CONFIG.
V-0-MAX™ Single Flush Receptacle	2610†			
V-0-MAX™ Single Flush Receptacle, Isolated Ground	2610-IG†			
Locking Plug, Black Nylon Body	2611	.385-.860	10-18	
Lighted Locking Plug, Black Nylon Body	2611-PLC	.385-.860	10-18	
Locking Plug, All Black for Stage and Studio	2611-B	.385-.860	10-18	L5-30R 
Lighted Locking Plug, All-Black Nylon Body	2611-PLB	.385-.860	10-18	
Locking Plug, Yellow Nylon Body	2611-CY	.385-.860	10-18	
Locking Connector, Black Nylon Body	2613	.385-.860	10-18	L5-30P 
Lighted Locking Connector, Black Nylon Body	2613-PLC	.385-.860	10-18	
Locking Connector, All Black for Stage and Studio	2613-B	.385-.860	10-18	
Lighted Locking Connector, All-Black Nylon Body	2613-PLB	.385-.860	10-18	
Locking Connector, Yellow Nylon Body	2613-CY	.385-.860	10-18	
Locking Flanged Inlet	2615			
Locking Flanged Outlet	2616			

30 AMP 250V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NEMA CONFIG.
V-0-MAX™ Single Flush Receptacle	2620†			
V-0-MAX™ Single Flush Receptacle, Isolated Ground	2620-IG†			
Locking Plug, Black Nylon Body	2621	.385-.860	10-18	
Locking Plug, All Black for Stage and Studio	2621-B	.385-.860	10-18	L6-30R 
Locking Plug, Yellow Nylon Body	2621-CY	.385-.860	10-18	
Locking Connector, Black Nylon Body	C2623	.385-.860	10-18	
Locking Connector, All Black for Stage and Studio	C2623-B	.385-.860	10-18	L6-30P 
Locking Connector, Yellow Nylon Body	C2623-CY	.385-.860	10-18	
Locking Flanged Inlet	2625F			
Locking Flanged Outlet	2626F			

†Uses stainless steel wallplate, Cat. No. 84020-40. For additional wallplate selections, please see Section G. For Corrosion Resistant Locking Devices, please check pages K2-K5. Weather-Resistant Boots for 30A Locking Plugs and Connectors are listed on page J20. All devices are UL Listed and CSA certified.



SPECIFICATIONS & FEATURES

- V-0-MAX™ Locking Receptacles carry a UL 94 V-0 Flammability Rating, the best rating of any material used in Industrial Locking Flush Receptacle available today
- Locking Plugs and Connectors feature heavy-duty construction for top performance in the environmental extremes of grueling industrial settings
- Flanged Inlets and Outlets are built to endure hard use with rugged nylon flanges that assure a smooth, flush fit and outstanding resistance to cracking and breaking

TESTING & CODE COMPLIANCE

- All receptacles, plugs, connectors, inlets and outlets are designed to meet NEMA WD-6, and ANSI C-73, and to meet/exceed UL 498 standards
- UL Fed Spec. Listed WC-596 (File #E-13399 — Cat. Nos. 2530, 2546, 2610, 2616, 2620, 2626F; File #E-13393 — Cat. Nos. 2531, 2533, 2545, 2611, 2613, 2615, 2621, 2623, 2625F)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Lifetime Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability per UL94 or CSA C22/06 Requirements
Operating Temperature: -40°C to 60°C

