



20 AMP Locking Devices

20 AMP 250V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NEMA CONFIG.
V-0-MAX™ Single Flush Receptacle	2320†			
V-0-MAX™ Single Flush Receptacle, Isolated Ground	2320-IG†			
Locking Plug, Black Nylon Body	2321	.385-.780	10-18	L6-20R
Locking Plug, Yellow Nylon Body	2321-CY	.385-.780	10-18	
Locking Connector, Black Nylon Body	2323	.385-.780	10-18	L6-20P
Locking Connector, Yellow Nylon Body	2323-CY	.385-.780	10-18	
Locking Flanged Inlet	2325			
Locking Flanged Outlet	2326			

20 AMP 277V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NEMA CONFIG.
V-0-MAX™ Single Flush Receptacle	2330†			
V-0-MAX™ Single Flush Receptacle, Isolated Ground	2330-IG†			
Locking Plug, Black Nylon Body	2331	.385-.780	10-18	L7-20R
Lighted Locking Plug, Black Nylon Body (check for availability)	2331-PLC	.385-.780	10-18	
Locking Connector, Black Nylon Body	2333	.385-.780	10-18	L7-20P
Lighted Locking Connector, Black Nylon Body (check for availability)	2333-PLC	.385-.780	10-18	
Locking Flanged Inlet	2335			
Locking Flanged Outlet	2336			

20 AMP 347V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NEMA CONFIG.
V-0-MAX™ Single Flush Receptacle*	3720†			
Locking Plug, Black Nylon Body*	3721	.385-.780	10-18	L24-20R
Locking Connector, Black Nylon Body*	3723	.385-.780	10-18	L24-20P
Locking Flanged Inlet*	3755			
Locking Flanged Outlet*	3756			

20 AMP 480V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NEMA CONFIG.
Single Flush Receptacle	2340†			
Single Flush Receptacle, Isolated Ground	2340-IG†			L8-20R
Locking Plug, Black Nylon Body	2341	.385-.780	10-18	L8-20P
Locking Connector, Black Nylon Body	2343	.385-.780	10-18	
Locking Flanged Inlet	2345			
Locking Flanged Outlet	2346			

†Uses stainless steel wallplate, Cat. No. 84020-40. For additional wallplate selections, please see Section G. For Corrosion Resistant Locking Devices, please check pages K2-K5. Weather-Resistant Boots for 20A Locking Plugs and Connectors are listed on page J20.



SPECIFICATIONS & FEATURES

- V-0-MAX™ Locking Receptacles carry a UL 94 V-0 Flammability Rating, the best rating of any material used in Industrial Locking Flush Receptacle available today
- Locking Plugs and Connectors feature heavy-duty construction for top performance in the environmental extremes of grueling industrial settings
- Flanged Inlets and Outlets are built to endure hard use with rugged nylon flanges that assure a smooth, flush fit and outstanding resistance to cracking and breaking

TESTING & CODE COMPLIANCE

- All receptacles, plugs, connectors, inlets and outlets are designed to meet NEMA WD-6, and ANSI C-73, and to meet/exceed UL 498 standards
- UL Fed Spec, Listed WC-596 (File #E-13399 — Cat. Nos. 2320, 2326, 2330, 2336, 3720, 3756, 2335, 2340, 2346; File #E-13393 — Cat. Nos. 2321, 2323, 2325, 2331, 2333, 2335, 3721, 3723, 3755, 2341, 2343, 2345)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Lifetime Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability per UL94 or CSA C22/06 Requirements
 Operating Temperature: -40°C to 60°C

