



## 20 AMP Locking Devices

### 20 AMP 125/250V 3-Pole 4-Wire Grounding

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NEMA CONFIG.
V-0-MAX™ Single Flush Receptacle	2410†			
V-0-MAX™ Single Flush Receptacle, Isolated Ground	2410-IG†			L14-20R
Locking Plug, Black Nylon Body	2411	.595-.895	10-18	
Locking Connector, Black Nylon Body	2413	.595-.895	10-18	L14-20P
Locking Flanged Inlet	2415			
Locking Flanged Outlet	2416			

### 20 AMP 3Ø 250V 3-Pole 4-Wire Grounding

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NEMA CONFIG.
V-0-MAX™ Single Flush Receptacle	2420†			
V-0-MAX™ Single Flush Receptacle, Isolated Ground	2420-IG†			L15-20R
Locking Plug, Black Nylon Body	2421	.595-.895	10-18	
Locking Connector, Black Nylon Body	2423	.595-.895	10-18	L15-20P
Locking Flanged Inlet	2425			
Locking Flanged Outlet	2426			

### 20 AMP 3Ø 480V 3-Pole 4-Wire Grounding

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NEMA CONFIG.
V-0-MAX™ Single Flush Receptacle	2430†			
V-0-MAX™ Single Flush Receptacle, Isolated Ground	2430-IG†			L16-20R
Locking Plug, Black Nylon Body	2431	.595-.895	10-18	
Locking Connector, Black Nylon Body	2433	.595-.895	10-18	L16-20P
Locking Flanged Inlet	2435			
Locking Flanged Outlet	2436			

### 20 AMP 3ØY 120/208V 4-Pole 4-Wire Non-Grounding

DESCRIPTION	CAT. NO.	CORD DIA. (inches)	WIRE GAUGE (stranded)	NEMA CONFIG.
Single Flush Receptacle★	2440†			
Locking Plug, Black Nylon Body★	2441	.595-.895	10-18	L18-20R
Locking Connector, Black Nylon Body★	2443	.595-.895	10-18	L18-20P
Locking Flanged Inlet★	2445			
Locking Flanged Outlet★	2446			

†Uses stainless steel wallplate, Cat. No. 84020-40. For additional wallplate selections, please see Section G. For Corrosion Resistant Locking Devices, please check pages K2-K5. Weather-Resistant Boots for 20A Locking Plugs and Connectors are listed on page J20. All devices are UL Listed. Also CSA certified except where indicated by ★



#### SPECIFICATIONS & FEATURES

- V-0-MAX™ Locking Receptacles carry a UL 94 V-0 Flammability Rating, the best rating of any material used in Industrial Locking Flush Receptacle available today
- Locking Plugs and Connectors feature heavy-duty construction for top performance in the environmental extremes of grueling industrial settings
- Flanged Inlets and Outlets are built to endure hard use with rugged nylon flanges that assure a smooth, flush fit and outstanding resistance to cracking and breaking

#### TESTING & CODE COMPLIANCE

- All receptacles, plugs, connectors, inlets and outlets are designed to meet NEMA WD-6, and ANSI C-73, and to meet/exceed UL 498 standards
- UL Fed Spec. Listed WC-596 (File #E-13399 — Cat. Nos. 2410, 2416, 2420, 2426, 2430, 2436, 2440, 2446; File #E-13393 — Cat. Nos. 2411, 2413, 2415, 2421, 2423, 2425, 2431, 2433, 2435, 2441, 2443, 2445)
- CSA Certified (File #LR-406)
- NOM Certified (#057)
- Backed by a Lifetime Warranty

#### MATERIAL CHARACTERISTICS

Environmental: Flammability per UL94 or CSA C22/06 Requirements  
Operating Temperature: -40°C to 60°C

