

**RM2500—RACK MOUNTABLE POWER DISTRIBUTION UNIT**



**Features**

- 12 AC power outlets (4 Front, 8 Rear), 15-amps
- Four front panel, transformer spaced, convenience outlets
- Power switch with guard, controls all 12 outlets
- Front panel circuit breaker
- Single-height rack mountable chassis (1U)
- 10-foot power cord
- Power indication light

**Technical Specifications**

*Designs and specifications are subject to change without notice due to product improvement.*

**PRODUCT SPECIFICATIONS:**

Agency Approval . . . . .	UL 1363 recognized , Resettable Power Tap
LED Indicators . . . . .	Yes (1)
Grounding Requirements . . . . .	Uses Electrical Ground
	#10 AWG for Primary
	#14 AWG for Isolated Loop
Recommended Ground Impedance . . . . .	< 0.5 Ohm
Width . . . . .	19"
Height . . . . .	1.75" (1U)
Depth . . . . .	4.5"
Weight . . . . .	4.81 lbs
Product Warranty . . . . .	Lifetime
Connected Equipment Warranty . . . . .	N/A

For up-to-date warranty information see our web site: [www.itwlinx.com](http://www.itwlinx.com)



**AC SPECIFICATIONS:**

SurgeGate Plus Circuitry . . . . .	N/A
Protect or Disconnect Circuitry . . . . .	N/A
Thermal Fusing . . . . .	N/A
Catastrophic Surge Circuit . . . . .	N/A
Over/Undervoltage Voltage Protection . . . . .	N/A
Overvoltage Voltage Shutoff . . . . .	N/A
Undervoltage Voltage Shutoff . . . . .	N/A
Single Pulse Energy Dissipation . . . . .	N/A
Peak Impulse Current . . . . .	N/A
EMI/RFI Noise Filtration . . . . .	N/A
Line Voltage . . . . .	120VAC, 50/60Hz
Initial Clamping Level . . . . .	N/A
UL 1449 Rating . . . . .	N/A
Protection Modes . . . . .	N/A
Maximum Current Rating . . . . .	15A (1800W)
Response Time . . . . .	N/A
Plug Configuration . . . . .	Straight
Number of Outlets . . . . .	12 (4 front, 8 rear)
Switched Outlets . . . . .	All
Cord Length . . . . .	10 ft

**SIGNAL LINE SURGE PROTECTION:**

**TELCO CIRCUIT PROTECTION**

Signal Perfect Circuitry . . . . .	N/A
Fuseless/Auto-Resettable . . . . .	N/A
Clamping Level . . . . .	N/A
Response Time . . . . .	N/A
Capacitance . . . . .	N/A
Suppression Modes . . . . .	N/A
Wires Protected . . . . .	N/A
Termination Type . . . . .	N/A

**COAX CIRCUIT PROTECTION**

Signal Perfect Circuitry . . . . .	N/A
Fuseless/Auto-Resettable . . . . .	N/A
Response Time . . . . .	N/A
Termination . . . . .	N/A
Antenna/Cable Lines Protected . . . . .	N/A
Antenna/Cable Clamping Level . . . . .	N/A
Antenna/Cable Attenuation . . . . .	N/A
Satellite Lines Protected . . . . .	N/A
Satellite Clamping Level . . . . .	N/A
Satellite Attenuation . . . . .	N/A

**LAN CIRCUIT PROTECTION**

Signal Perfect Circuitry . . . . .	N/A
Fuseless/Auto-Resettable . . . . .	N/A
Performance Rating . . . . .	N/A
Clamping Level . . . . .	N/A
Response Time . . . . .	N/A
Wires Protected . . . . .	N/A
Termination Type . . . . .	N/A

**Applications:**

- Telephone Systems
- Workstations
- Printers
- Fax Machines
- Copiers
- TVs / VCRs
- Cameras
- Access Controls
- Alarms

**Ordering Information**

ITW Linx Part Number	Description
<b>RM2500</b>	8-outlet Rack-mountable AC Power Distribution Unit, 12-outlets (4 front, 8 rear) Fits standard 19" Racks / Cabinets.

