

Porcelain Mogul Base Lampholders

With Leads*

DESCRIPTION	CAT. NO.	RATING	OUTSIDE DIAMETER	OVERALL HEIGHT
Keyless, Single Circuit. For high pressure sodium lamps up to 1000 watts. 8-32 Mounting Screws on 1 $\frac{3}{8}$ " Centers	8746	1500W 600V 5KV Pulse-rated	2 $\frac{1}{8}$	3 $\frac{1}{64}$
Keyless, Single Circuit. Position-oriented. For Super Metalarc HID lamps. 8-32 Mounting Screws on 1 $\frac{3}{8}$ " Centers	8750	1500W 600V	2 $\frac{5}{32}$	2 $\frac{39}{64}$
Keyless, Single Circuit. For high-pressure sodium lamps up to 400 watts. 8-32 Mounting Screws on 1 $\frac{3}{8}$ " Centers	8756	1500W 600V 4KV Pulse-rated	2 $\frac{5}{32}$	2 $\frac{39}{64}$
Low Pressure Sodium. For use with all single-end bayonet base low pressure sodium lamps★	8806	660W 1000V	1 $\frac{3}{8}$	1 $\frac{5}{8}$

*Leads types, lengths and ratings vary with the end use applications. Standard leads as well as variations available on inquiry.

Screw Terminals

DESCRIPTION	CAT. NO.	RATING	OUTSIDE DIAMETER	OVERALL HEIGHT
Keyless; 2-Piece; Single-Pole★	8765	1500W 600V	2 $\frac{1}{4}$	2 $\frac{23}{64}$
Keyless; Single Circuit with 8-32 Lock Nuts on 1 $\frac{3}{8}$ " Centers. Die-cast caps available upon request	8694	1500W 600V	2 $\frac{5}{32}$	2 $\frac{11}{16}$

All devices are UL Listed. Also CSA Certified except where indicated by★



8756



8806

SPECIFICATIONS & FEATURES

- Cat. No. 8746 – Porcelain body gray glazed with ceramic arc shield; Cat. No. 8750 – Porcelain body yellow glazed
- All other mogul listed have white glazed porcelain body
- Copper-alloy nickel-plated screw shell

TESTING & CODE COMPLIANCE

- UL Listed (File #E-13402)
- CSA Certified (File #LR-1863)

