Porcelain Snap-In Lampholders — Medium Base *Screw Terminals*

DESCRIPTION	CAT. NO.	RATING	OD	ОН
1-Piece, Front Mounted. 1/4" Shoulder. Panel Thickness: .025 –.062"	8880	660W 250V	1 ¹¹ /16	11/2
1-Piece, Front Mounted. Shallow Back. Panel Thickness: .030 –.062"	8875	660W 250V	1 ¹¹ / ₁₆	111/16

Porcelain Keyless Lampholders Commercial Units — Medium Base

Single Circuit Screw Terminals

DESCRIPTION	CAT. NO.	RATING	OD	ОН
Straight Body with Cap. Screw Terminals.	10045	660W 250V	11/2	21/8
Beaded Body for 11/2" Clamp Style Shadeholder with Cap.	10065	660W 250V	Body 11/2	21/8
Screw Terminals.			Bead 15/8	
Adjustable Glass Retaining Ring with Cap and Ring Nut. Screw Terminals.	20070	660W 250V	21/4 ringnu	t ——
Straight Body with Leads. No. 18 AWG 105°C Plastic; 9" Long, Stripped 3/4" with Two 6/32 Mounting Screws	10085	660W 250V	11/2	111/16



DESCRIPTION	CAT. NO.	RATING	OD	ОН	Π
1-Piece, Front Mounted for Fixture or Sign Use. Tapped 8-32 Bushings, Mounting Centers 113/16".	9885	660W 600V	15/8	1 7/16	
2-Piece, Ring Type	9350	660W 250V	13/4	13/8	
1-Piece with Removable Strap★	8871	660W 250V	111/16	19/16	
Fixture Pan Lampholder with 1/8" IPS Hickey	3152-8	660W 250V	13/8	17/16	

Leads

DESCRIPTION	CAT. NO.	RATING	OD	ОН
2-Piece Ring Type with Leads: No. 18 AWG, 105°C Plastic; 9" Long, Stripped 3/4"	8101	660W 250V	13/4	13/8
Angle Pan with Leads: No. 18 AWG Type AF 150°C Plastic; 9" Long, Stripped 3/4"	18315	660W 250V		
Removable Bracket with Leads	8052-1	660W 250V	13/8	17/16

Two-Piece Pull Chain

DESCRIPTION	CAT. NO.	RATING	OD	ОН
Ring Type; Screw Terminals; Gasket Furnished★	9814	250W 250V	1 ¹³ /16	1 ¹³ /16

All devices are UL Listed. Also CSA Certified except where indicated by★





SPECIFICATIONS & FEATURES

- Suitable for a wide variety of fixtures, signs and displays
- Unglazed base and ring on two-piece lampholders
- Gasket supplied with two-piece ring type rated at 90°C dry maximum

TESTING & CODE COMPLIANCE

- UL Listed (File #E-3810)
- CSA Certified (File #LR-1863)

