

## Phenolic Keyless Fixture — Medium Base

### Screw Terminals

DESCRIPTION	CAT. NO.	RATING
Permanent Bracket. Terminal Screws Backed Out and Staked	3352-1	660W 250V
Same as 3352-1, with Shorter Bracket	3352-F	660W 250V
Removable Hickey. Terminal Screws Backed Out and Staked	3352-8	660W 250V

Hickeys and brackets are available in various types and sizes. Consult a Leviton representative for more information.

## Porcelain Keyless, Side-Mounted — Medium Base

### Screw Terminals

DESCRIPTION	CAT. NO.	RATING
Single Lampholder w/Side Outlet Bushing— $\frac{1}{8}$ IPS	10091	660W 250V
Twin Lampholder w/Bushed Flange— $\frac{1}{8}$ IPS	4010	660W 250V
Twin Lampholder w/Single Outlet Bushing— $\frac{1}{8}$ IPS	4005	660W 250V
Same as 4005 with $\frac{3}{8}$ IPS Bushing	4006	660W 250V

All bushings are tapped and have set screw

## Lampholders for Recessed Single Contact Lamps

DESCRIPTION	CAT. NO.	RATING
Front Flange Mount. Standard Leads are No. 18 AWG, Type SEW-2, 200°C, 18" Long, Stripped $\frac{3}{4}$ "	554	3000W 600V
Rear Flange Mount. Same Leads and Specs as No. 554	555	3000W 600V

## Candle Sockets, Bottom Turn Knob — Medium Base

### Screw Terminals

DESCRIPTION	CAT. NO.	RATING
Three-light, two-piece phenolic husk. Lighting sequence: LO-MED-HI-OFF★	4063	250W 250V

All devices are UL Listed. Also CSA Certified except where indicated by ★

### SPECIFICATIONS & FEATURES

- Cat. No. 3352 lampholder bodies have wire-ways
- Side-Mounted lampholders are white glazed porcelain with copper-alloy screwshell
- Recessed Single-Contact lampholders have porcelain body with nickel-plated steel housing

### TESTING & CODE COMPLIANCE

- UL Listed (File #E-3810)
- CSA Certified (File #LR-1863)

