

## Candle Sockets, Bottom Turn Knob — Medium Base

*Screw Terminals*

DESCRIPTION	CAT. NO.	RATING
1-Piece Phenolic Body; 2 Leg Bracket; Single Light; Removable Interior; Knurl Nut and Lock Nut	4155	660W 250V
2-Piece Phenolic Husk & Removable Interior Husk; Single Light; Knurl Nut	4158	660W 250V



## Candle Sockets, Keyless\* — Medium Base

*Fiber-Disc Body, Screw Terminals*

DESCRIPTION	CAT. NO.	RATING
Solid Hickey, 2" Overall Height	8684	660W 250V
Adjustable Hickey. Overall Height: 4 – 5 3/4"	9800	660W 250

\*Insulating paper liner pushes down against hickey projections.

NOTE: These items are designed for use with standard socket candle tubes (1 15/16" dia.) and require a minimum of 13/16" dia. flat bottom of candle cup for clearance.



## Candle Sockets, Phenolic — Medium Base

*With Removable Turn Knob, Screw Terminals*

DESCRIPTION	CAT. NO.	RATING
Removable Knob (Short Type), Adjustable Hickey. Overall Height: 4 – 5 1/2"	9805*	250W 250V
Removable Knob, Removable 1-Leg Hickey. Overall Height: 2 7/16"	9805-A*	250W 250V

NOTE: These items are designed for use with standard socket candle tubes (1 15/16" dia.) and require a minimum of 13/16" dia. flat at bottom of candle for clearance.

## Candelabra Base, Keyless\*

DESCRIPTION	CAT. NO.	RATING
Screw Terminals; Solid Hickey. Overall Height: 2"	10025	75W 125V
Screw Terminals; Solid Hickey. Overall Height: 1 1/2"	10027	75W 125V
Screw Terminals; Adjustable Hickey: 3 1/4 – 4 3/4"	10026	75W 125V
Double Snap-In Spring Clips. Height of socket from panel is 1". Leads are No. 18 AWG 105°C plastic, 24" long, stripped 1/2"	10014-800	75W 125V

\*7/8" candle tube. All hickeys tapped 1/8 IPS.

All devices are UL Listed and CSA Certified.

### SPECIFICATIONS & FEATURES

- Candle sockets for single-light applications
- Fiber Disc Body for use with standard candle tubes
- Spring-tempered steel clip holds Cat. No. 10014-800 socket rigidly in place

### TESTING & CODE COMPLIANCE

- UL Listed (File #E-3810; E-13400)
- CSA Certified (File #LR-1863)

