Candle Sockets, Bottom Turn Knob — Medium Base Screw Terminals

| DESCRIPTION | CAT. NO. | RATING |
|---|----------|-----------|
| 1-Piece Phenolic Body; 2 Leg Bracket; Single Light; Removable Interior; Knurl Nut and Lock Nut | 4155 | 660W 250V |
| 2-Piece Phenolic Husk & Removable Interior Husk; Single Light; Knurl Nut | 4158 | 660W 250V |

Candle Sockets, Keyless*— Medium Base Fiber-Disc Body, Screw Terminals

| DESCRIPTION | CAT. NO. | RATING |
|--|----------|-----------|
| Solid Hickey, 2" Overall Height | 8684 | 660W 250V |
| Adjustable Hickey. Overall Height: 4 – 53/4" | 9800 | 660W 250 |

^{*}Insulating paper liner pushes down against hickey projections.

NOTE: These items are designed for use with standard socket candle tubes (115/16" dia.) and require a minimum of 13/16" dia. flat bottom of candle cup for clearance.

Candle Sockets, Phenolic — Medium Base With Removable Turn Knob, Screw Terminals

| DESCRIPTION | CAT. NO. | RATING |
|---|----------|-----------|
| Removable Knob (Short Type), Adjustable Hickey. Overall Height: $4-5^{1/2}$ " | 9805* | 250W 250V |
| Removable Knob, Removable 1-Leg Hickey. Overall Height: 27/16" | 9805-A* | 250W 250V |

NOTE: These items are designed for use with standard socket candle tubes (115/16" dia.) and require a minimum of 13/16" dia. flat at bottom of candle for clearance.

Candelabra Base, Keyless*

| DESCRIPTION | CAT. NO. | RATING | |
|---|-----------|----------|--|
| Screw Terminals; Solid Hickey. Overall Height: 2" | 10025 | 75W 125V | |
| Screw Terminals; Solid Hickey. Overall Height: 11/2" | 10027 | 75W 125V | |
| Screw Terminals; Adjustable Hickey: 31/4 – 43/4" | 10026 | 75W 125V | |
| Double Snap-In Spring Clips. Height of socket from panel is 1". Leads are No. 18 AWG 105°C plastic, 24" long, stripped ½" | 10014-800 | 75W 125V | |

^{*7/8&}quot; candle tube. All hickeys tapped 1/8 IPS.

All devices are UL Listed and CSA Certified.





SPECIFICATIONS & FEATURES

- Candle sockets for single-light applications
- Fiber Disc Body for use with standard candle tubes
- Spring-tempered steel clip holds Cat. No. 10014-800 socket rigidly in place

TESTING & CODE COMPLIANCE

- UL Listed (File #E-3810; E-13400)
- CSA Certified (File #LR-1863)





