

PJ Junior Duty Series Grips are indispensable tools for electricians with small job requirements. They are used to connect insulated wire bundles to pulling tape or to pull wire rope through conduit.


## Pulling Grips—PJ Series S

Single Weave, Flexible Eye, Junior Duty

CAT. NO.	CABLE DIA. RANGE (INCHES)	APPROXIMATE BREAK STRENGTH*	MESH LENGTH (INCHES)
L8500	0.25–0.36	1,700	5
L8501	0.37–0.49	1,700	7
L8502	0.50–0.61	1,700	8
L8503	0.62–0.74	2,800	10
L8504	0.75–0.99	4,100	10
L8505	1.00–1.24	4,100	12

## Single Weave, Flexible Eye, Junior Duty—Kit

KIT CAT. NO.	KIT INCLUDES ONE EACH OF CAT. NO.
L8510	L8500
	L8501
	L8502
	L8503
	L8504
	L8505



PL Light Duty Grips are the most economical pulling grips for many applications, such as industrial plant wiring, rewiring, and underground electrical pulls.

## Pulling Grips—PL Series S

Single Weave, Flexible Rope Eye, Light Duty, Short

CAT. NO.	CABLE DIA. RANGE (INCHES)	APPROXIMATE BREAK STRENGTH*	MESH LENGTH (INCHES)
L8511	0.50–0.61	3,400	12
L8512	0.62–0.74	4,100	14
L8513	0.75–0.99	4,100	14
L8514	1.00–1.24	5,800	16.5
L8515	1.25–1.49	5,800	17
L8516	1.50–1.74	7,500	20
L8517	1.75–1.99	10,000	23
L8518	2.00–2.49	10,000	23
L8519	2.50–2.99	13,000	23

## Single Weave, Flexible Rope Eye, Light Duty, Medium

CAT. NO.	CABLE DIA. RANGE (INCHES)	APPROXIMATE BREAK STRENGTH*	MESH LENGTH (INCHES)
L8523	0.50–0.61	3,400	16
L8524	0.62–0.74	4,100	16
L8525	0.75–0.99	4,100	20
L8526	1.00–1.24	7,500	20
L8527	1.25–1.49	7,500	22
L8528	1.50–1.99	7,500	25
L8529	2.00–2.49	10,000	26
L8530	2.50–2.9	13,000	28
L8531	3.00–3.49	16,200	30
L8532	3.50–3.99	19,400	32

## Single Weave, Flexible Rope Eye, Light Duty, Medium—Kit

KIT CAT. NO.	KIT INCLUDES ONE EACH OF CAT. NO.
L8540	L8525
	L8526
	L8528
	L8529

\*To determine workload safety factor, divide approximate break strength by 5. See page Q5 for strength information.

