



Pulling Grips—P Series S

Leviton's *P Series* is recommended for heavy or rugged applications, and is ideally suited for overhead and underground installations. They are offered in short, standard or long mesh lengths.

Single/Double Weave, Bale Eye, Medium Duty, Short

CAT. NO.	CABLE DIA. RANGE (INCHES)	NOMINAL GRIP SIZE	APPROX. BREAK STRENGTH*	LENGTH (INCHES)		EYE SIZE (INCHES)
				BALE (DIM. A)	MESH (DIM. M)	
L8551	0.50–0.61	0.55	4,500	8	21	7/32
L8552	0.62–0.74	0.68	5,600	8	24	1/4
L8553	0.75–0.99	0.87	6,800	8	24	1/4
L8554	1.00–1.49	1.25	9,600	9	24	5/16
L8555	1.50–1.99	1.75	16,400	11	24	7/16
L8556	2.00–2.49	2.25	18,500	12	24	7/16
L8557	2.50–2.99	2.75	24,500	12	24	1/2
L8558	3.00–3.49	3.25	24,500	14	24	1/2
L8559	3.50–3.99	3.75	31,000	14	26	5/8

Single/Double Weave, Bale Eye, Medium Duty, Standard

CAT. NO.	CABLE DIA. RANGE (INCHES)	NOMINAL GRIP SIZE	APPROX. BREAK STRENGTH*	LENGTH (INCHES)		EYE SIZE (INCHES)
				BALE (DIM. A)	MESH (DIM. M)	
L8563	0.75–0.99	0.87	6,800	9	36	1/4
L8564	1.00–1.49	1.25	9,600	9	36	5/16
L8565	1.50–1.99	1.75	16,400	11	36	7/16
L8566	2.00–2.49	2.25	18,500	12	36	7/16
L8567	2.50–2.9	2.75	24,500	12	36	1/2
L8568	3.00–3.49	3.25	24,500	14	36	1/2
L8569	3.50–3.99	3.75	31,000	14	40	5/8

Single/Double Weave, Bale Eye, Medium Duty, Standard—Kit

KIT CAT. NO.	KIT INCLUDES ONE EACH OF CAT. NO.
L8560	L8563
	L8564
	L8565
	L8566

Single/Double Weave, Bale Eye, Heavy Duty, Long

CAT. NO.	CABLE DIA. RANGE (INCHES)	NOMINAL GRIP SIZE	APPROX. BREAK STRENGTH*	MESH DIM. M (INCHES)
L8572	0.75–0.99	0.87	8,100	48
L8573	1.00–1.49	1.25	11,600	48
L8574	1.50–1.99	1.75	19,400	48
L8575	2.00–2.49	2.25	19,400	48
L8576	2.50–2.99	2.75	25,900	48
L8577	3.00–3.49	3.25	25,900	48
L8578	3.50–3.99	3.75	32,400	48

Note: See installation instructions supplied with grip for recommended swivels, links and clamps or accessories listing.

*To determine workload safety factor, divide approximate break strength by 5. See page Q5 for strength information.