

Deluxe Cord Grips U* R*

Deluxe Cord Grips are woven of stainless steel mesh with an anodized aluminum body for corrosion resistance. They are offered in Single/Double Weave construction to help absorb direct pull, resist flexing and binding, and eliminate strain. Aluminum fittings are offered in a variety of NPT thread sizes. They are recommended for indoor or outdoor use where moisture may be present in the wiring of pendant stations, processing equipment, hand tools, and extension cord sets. They are UL Listed and CSA Certified. Deluxe Cord Grips are suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2. They are also suitable for use in wet locations as long as a listed sealing ring is used between the box and the fitting.

Single/Double Weave

CAT. NOS. STRAIGHT MALE	90° MALE	45° MALE	STRAIGHT FEMALE	CABLE DIA. RANGE (INCHES)	NPT SIZE
L7701				.187-.250	
L7702			L7821	.250-.312	
L7703			L7822	.312-.375	3/8"
L7704			L7823	.375-.437	
L7705	L7761	L7801	L7824	.187-.250	
L7706	L7762	L7802	L7825	.250-.375	
L7707	L7763	L7803	L7826	.375-.500	1/2"
L7708	L7764	L7804	L7827	.500-.625	
L7709				.625-.750	
L7711	L7765	L7805	L7828	.250-.375	
L7712	L7766	L7806	L7829	.375-.500	
L7700	L7767	L7807	L7831	.500-.625	3/4"
L7713	L7768	L7808	L7832	.625-.750	
L7714				.750-.875	
L7715	L7769			.437-.562	
L7716	L7771	L7809	L7833	.562-.687	
L7717	L7772	L7811	L7834	.625-.750	1"
L7718	L7773	L7812	L7835	.750-.875	
L7719	L7774	L7813	L7836	.875-1.000	
L7721				1.000-1.125	
L7722				1.125-1.250	
L7723	L7775			.750-.875	
L7724	L7776			.875-1.000	
L7725	L7777	L7810		1.000-1.125	1-1/4"
L7726	L7778			1.125-1.250	
L7727	L7779	L7820		1.250-1.375	
L7728	L7781			.750-.875	
L7729	L7782			.875-1.000	
L7731	L7783			1.000-1.125	1-1/2"
L7732	L7784			1.125-1.250	
L7733	L7785			1.250-1.375	
L8011				1.312-1.437	
L7770				1.437-1.562	
L7750				1.562-1.687	
L7760				1.687-1.812	
L7780				1.750-1.875	
L7734	L7786			1.250-1.375	
L7735	L7787			1.437-1.562	
L7736	L7788			1.500-1.625	2"
L7737	L7789			1.625-1.750	
L7738	L7791			1.750-1.875	
L8012				1.812-1.937	
L8013				1.937-2.062	
L7720				2.062-2.187	
L7730				2.187-2.312	
L7739				1.688-1.812	
L7741				1.812-1.937	
L7742				1.937-2.062	2-1/2"
L7743				2.062-2.187	
L7744				2.187-2.312	
L7740				2.312-2.437	
L7745				1.750-1.875	
L7746				1.875-2.000	
L7747				2.000-2.125	
L7748				2.125-2.250	
L7749				2.187-2.312	3"
L7751				2.312-2.437	
L7752				2.437-2.625	
L7753				2.625-2.812	
L7754				2.812-3.000	
L7755				3.000-3.250	



Straight—Male



90°—Male



45°—Male



Straight—Female

Sold by:

TWAcomm.com
http://www.TWAcomm.com
Toll Free: (877) 892-2666