Deluxe Cord Grips U* R*

Deluxe Cord Grips are woven of stainless steel mesh with an anodized aluminum body for corrosion resistance. They are offered in Single/Double Weave construction to help absorb direct pull, resist flexing and binding, and eliminate strain. Aluminum fittings are offered in a variety of NPT thread sizes. They are recommended for indoor or outdoor use where moisture may be present in the wiring of pendant stations, processing equipment, hand tools, and extension cord sets. They are UL Listed and CSA Certified. Deluxe Cord Grips are suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2. They are also suitable for use in wet locations as long as a listed sealing ring is used between the box and the fitting.

Single/Double Weave

CAT. NOS. STRAIGHT MALE	90° MALE	45° MALE	STRAIGHT FEMALE	CABLE. DIA. RANGE (INCHES)	NPT SIZE
L7701	—	—	—	.187–.250	
L7702	—	—	**L7821**	.250–.312	
L7703	—	—	**L7822**	.312–.375	3/8"
L7704	—	—	**L7823**	.375–.437	
L7705	**L7761**	**L7801**	**L7824**	.187–.250	
L7706	**L7762**	**L7802**	**L7825**	.250–.375	
L7707	**L7763**	**L7803**	**L7826**	.375–.500	1/2"
L7708	**L7764**	**L7804**	**L7827**	.500–.625	
L7709	—	—	—	.625–.750	
L7711	**L7765**	**L7805**	**L7828**	.250–.375	
L7712	**L7766**	**L7806**	**L7829**	.375–.500	
L7700	**L7767**	**L7807**	**L7831**	.500–.625	3/4"
L7713	**L7768**	**L7808**	**L7832**	.625–.750	
L7714	—	—	—	.750–.875	
L7715	**L7769**			.437–.562	
L7716	**L7771**	**L7809**	**L7833**	.562–.687	
L7717	**L7772**	**L7811**	**L7834**	.625–.750	1"
L7718	**L7773**	**L7812**	**L7835**	.750–.875	
L7719	**L7774**	**L7813**	**L7836**	.875–1.000	
L7721	—	—	—	1.000–1.125	
L7722	—	—	—	1.125–1.250	
L7723	**L7775**	—	—	.750–.875	
L7724	**L7776**	—	—	.875–1.000	
L7725	**L7777**	**L7810**	—	1.000–1.125	1-1/4"
L7726	**L7778**		—	1.125–1.250	
L7727	**L7779**	**L7820**	—	1.250–1.375	
L7728	**L7781**	—	—	.750–.875	
L7729	**L7782**	—	—	.875–1.000	
L7731	**L7783**	—	—	1.000–1.125	1-1/2"
L7732	**L7784**	—	—	1.125–1.250	
L7733	**L7785**	—	—	1.250–1.375	
L8011	—	—	—	1.312–1.437	
L7770	—	—	—	1.437–1.562	
L7750	—	—	—	1.562–1.687	
L7760	—	—	—	1.687–1.812	
L7780	—	—	—	1.750–1.875	
L7734	**L7786**	—	—	1.250–1.375	
L7735	**L7787**	—	—	1.437–1.562	
L7736	**L7788**	—	—	1.500–1.625	2"
L7737	**L7789**	—	—	1.625–1.750	
L7738	**L7791**	—	—	1.750–1.875	
L8012	—	—	—	1.812–1.937	
L8013	—	—	—	1.937–2.062	
L7720	—	—	—	2.062–2.187	
L7730	—	—	—	2.187–2.312	
L7739	—	—	—	1.688–1.812	
L7741	—	—	—	1.812–1.937	
L7742	—	—	—	1.937–2.062	2-1/2"
L7743	—	—	—	2.062–2.187	
L7744	—	—	—	2.187–2.312	
L7740	—	—	—	2.312–2.437	
L7745	—	—	—	1.750–1.875	
L7746	—	—	—	1.875–2.000	
L7747	—	—	—	2.000–2.125	
L7748	—	—	—	2.125–2.250	
L7749	—	—	—	2.187–2.312	3"
L7751	—	—	—	2.312–2.437	
L7752	—	—	—	2.437–2.625	
L7753	—	—	—	2.625–2.812	
L7754	—	—	—	2.812–3.000	
L7755	—	—	—	3.000–3.250	

Straight—Male

90°—Male

45°—Male

Straight—Female

Sold by:
TWAcomm.com
http://www.TWAcomm.com
Toll Free: (877) 892-2666